

---

# GROUNDWATER MONITORING PLAN

Gibbons Creek Steam Electric Station, Grimes County, Texas

*Prepared for:*

**Texas Municipal Power Agency**

12824 FM 244 Road

Anderson, Texas

*Prepared by:*

**Amec Foster Wheeler Environment & Infrastructure, Inc.**

3755 S. Capital of Texas Highway, Ste. 375

Austin, Texas 78704

(512) 795-0360

October 16, 2017

Project 6706150060

---

## TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
1.1	MONITORING OBJECTIVES.....	1
2.0	GROUNDWATER MONITORING Network.....	1
2.1	SITE F LANDFILL MONITORING WELL NETWORK .....	1
2.1.2	HYDROGEOLOGIC SETTING .....	1
2.1.3	MONITORING WELL LOCATIONS AND DESIGNATED USE.....	2
2.2	SCRUBBER SLUDGE POND/ASH PONDS MONITORING WELL NETWORK.....	2
2.2.1	HYDROGEOLOGIC SETTING .....	2
2.2.3	MONITORING WELL LOCATIONS AND DESIGNATED USE.....	3
2.3	MONITORING FREQUENCY.....	3
2.4	ANALYTICAL PARAMETERS .....	3
3.0	FIELD SAMPLING PROCEDURES.....	5
3.1	GROUNDWATER LEVEL MONITORING .....	5
3.2	GROUNDWATER QUALITY MONITORING.....	7
3.2.1	Groundwater Sample Collection Procedures.....	7
3.2.2	Field Parameter Measurements and Stabilization.....	9
3.2.3	Sample Collection .....	9
3.2.4	Sample Containers, Preservation, and Holding Times.....	10
3.3	DOCUMENTATION OF FIELD ACTIVITIES .....	11
3.4	SAMPLE IDENTIFICATION, DOCUMENTATION, AND CUSTODY .....	12
3.5	SAMPLE PACKING AND TRANSPORT .....	13
3.6	FIELD EQUIPMENT CALIBRATION .....	13
3.7	SAMPLE DOCUMENTATION AND RECORDS.....	14
3.8	EQUIPMENT DECONTAMINATION .....	14
3.9	HANDLING AND DISPOSITION OF INVESTIGATION-DERIVED WASTES .....	14
4.0	QUALITY ASSURANCE/QUALITY CONTROL.....	14
4.1	STANDARD OPERATING PROCEDURES .....	14
4.2	SAMPLE ANALYSIS VALIDATION.....	14
4.2.1	Quality Assurance and Quality Control Samples .....	15
4.2.2	Data Review Procedures.....	15

## LIST OF FIGURES

Figure 1.1	Site Plan
Figure 2.2	Site F Landfill Monitoring Well Network
Figure 2.3	Ash Ponds and Scrubber Sludge Pond Monitoring Well Network

## LIST OF TABLES

Table 2-1	Well Construction Details
Table 2-2	Constituents for Detection and Assessment Monitoring under the CCR Rule
Table 3-1	Field Parameter Stabilization Criteria for Monitor Well Purging and Sampling
Table 3-2	Sample Parameter Groups, Container Sizes, Preservation Methods, Holding Times

## LIST OF APPENDICES

Appendix A	Borehole Logs and Well Installation Diagrams
Appendix B	Field Sampling, Water Level Measurement, Meter Calibration, and COC Forms

## 1.0 INTRODUCTION

Groundwater monitoring will be conducted at the active coal combustion residual landfill and ponds at the Texas Municipal Power Agency (TMPA) Gibbons Creek Steam Electric Station (GCSES) to comply with the requirements of the Coal Combustion Residuals (CCR) regulations found in 40 CFR parts 257 and 261. This groundwater monitoring plan includes procedures to be used to collect samples to comply with these regulations.

### 1.1 Monitoring Objectives

The groundwater monitoring objectives are as follows:

- Collect representative samples from the uppermost aquifer at the following designated CCR units (Figure 1.1)
  - Site F Landfill
  - Ash Ponds
  - Scrubber Sludge Pond
- Measure groundwater levels in the uppermost aquifer
- Determine groundwater flow rate and direction in the uppermost aquifer
- Determine background groundwater quality
- Evaluate whether a statistically significant increase over background levels has been detected for Appendix III to Part 257 constituents at monitoring wells at the waste boundary for CCR units

## 2.0 GROUNDWATER MONITORING NETWORK

Groundwater monitoring networks have been established at the three CCR units at the GCSES; the Site F Landfill, Ash Ponds, and Scrubber Sludge Pond. The monitoring networks are shown in Figures 2.1 and 2.2, respectively. Construction details for the monitoring wells that comprise the networks are summarized in Table 2-1. Borehole and well construction logs are provided in Appendix A.

### 2.1 SITE F LANDFILL MONITORING WELL NETWORK

#### 2.1.2 HYDROGEOLOGIC SETTING

The Site F Landfill is underlain by stratified, heterogeneous layers of clays, silts, and sands of varying thicknesses. Sandstone was observed at some boring locations as well. The elevation of screened intervals in monitoring wells ranges from approximately 250 feet to 220 feet above mean sea level (amsl). The screened intervals are generally completed in silty sands (SM) with intervals of clayey sands and silts.

Groundwater investigations by others (ERM, 2013, 2014) indicated that groundwater flow direction beneath the Site F Landfill was generally northwest to southeast. Groundwater level monitoring

completed by Amec Foster Wheeler Environment & Infrastructure, Inc. (Amec Foster Wheeler), using an expanded monitoring network confirmed the general groundwater flow gradient from northwest to southeast, but influence from the Gibbons Creek Reservoir on groundwater flow direction was observed.

### **2.1.3 MONITORING WELL LOCATIONS AND DESIGNATED USE**

The Site F Landfill monitoring well network is shown on Figure 2.1 and consists of wells installed by Amec Foster Wheeler in 2016 and 2017, and wells installed by Black and Veatch in 1988.

The Site F Landfill monitoring network consists of the following wells:

- Background Well: MNW-18
- Boundary Wells: SFL MW-2, SFL MW-3, SFL MW-4, SFL MW-5, SFL MW-6, SFL MW-7, and MNW-15
- Water Level Only Wells: MNW-11, MNW-17, MNW-16

## **2.2 SCRUBBER SLUDGE POND/ASH PONDS MONITORING WELL NETWORK**

### **2.2.1 HYDROGEOLOGIC SETTING**

The Ash Ponds and Scrubber Sludge Pond are underlain by interbedded silty and sandy clays, clay, clayey sands and silty sand. Hard sandstone intervals are intermittently present, as are thin lenses of lignite or lignitic silts. Groundwater is considered confined to semi-confined, and generally encountered at depths of 30 to 40 feet below ground surface. The elevation of monitoring well screened intervals ranges from approximately 240 ft amsl to 220 ft amsl.

Groundwater investigations by others (ERM, 2013, 2014) indicated that groundwater flow directions are controlled by the local topography and a groundwater divide exists between the Ash Ponds and the Scrubber Sludge Pond. Groundwater level monitoring completed by Amec Foster Wheeler using an expanded monitoring network confirms the presence of the groundwater divide and flow direction to the east beneath the Ash Ponds. Groundwater flows to the southwest beneath the Scrubber Sludge Pond. The background groundwater quality monitoring well is located on the groundwater divide and provides background data for both networks.

Water level measurements in the most recently-installed monitoring well, AP MW-6, may be anomalously lower than the rest of the monitoring well network. Consequently, temporal trends in the well will be evaluated moving forward to assess whether the conceptual flow model should be revised.

### 2.2.3 MONITORING WELL LOCATIONS AND DESIGNATED USE

The Ash Ponds and Scrubber Sludge Pond monitoring well networks are shown on Figure 2-2, and consist of both monitoring wells and piezometers. The piezometers are used for water level data collection only, groundwater quality samples are only collected from monitoring wells.

The monitoring well network includes:

- Background Well: SSP/AP MW-1 (used as background for both The Ash Ponds and Scrubber Sludge Pond networks)
- Scrubber Sludge Pond Boundary Wells: SSP MW-2, SSP MW-3, SSP MW-4
- Ash Ponds Boundary Wells: AP MW-1D, AP MW-3, AP MW-4, AP MW-5
- Ash Ponds Piezometers: AP PZ-1, AP PZ-2, AP PZ-3, AP PZ-4

### 2.3 MONITORING FREQUENCY

The CCR regulations require the collection and analysis of a minimum of eight independent samples from each background and downgradient well for the constituents listed in Appendix III and IV of Part 257 by no later than October 17, 2017. In order to meet this requirement, monitoring was conducted on a bimonthly (every two months) schedule. Groundwater monitoring events have occurred in June 2016, August 2016, October 2016, December 2016, February 2017, April 2017, June 2017, and August 2017. Additional groundwater monitoring events were scheduled, as wells were added to the monitoring network.

Semiannual monitoring frequency for *detection monitoring* will be implemented after October 2017. The CCR rules allow for reducing the monitoring frequency to annually, based on the availability of groundwater. If annual monitoring is justified by the site-specific conditions, the sampling frequency will be adjusted.

### 2.4 ANALYTICAL PARAMETERS

As noted above, eight independent groundwater samples were collected prior to October 17, 2017, and analyzed for the Appendix III and IV constituents designated in Part 257, which are listed in Table 2-2.

**Table 2-2**  
**Constituents for Detection and Assessment**  
**Monitoring under the CCR Rule**

<b>Constituent</b>	<b>MCL (mg/L)</b>	<b>Analytical Method</b>	<b>Reporting Limit</b>
<b>Appendix III to Part 257 - Constituents for Detection Monitoring</b>			
Boron	--	E200.7	0.05
Calcium	--	E200.7	1
Chloride	--	E300.0	1
Fluoride	4	A4500-F C	0.1
Sulfate	--	E300.0	1
pH (std)	--	A4500-H B	0.1
Total Dissolved Solids	--	A2540 C	40
<b>Appendix IV to Part 257 - Constituents for Assessment Monitoring</b>			
Antimony	0.006	E200.7	0.05
Arsenic	0.01	E200.8	0.01
Barium	2	E200.7	0.01
Beryllium	0.004	E200.7	0.001
Cadmium	0.005	E200.7	0.01
Chromium (Total)	0.1	E200.7	0.01
Cobalt	--	E200.7	0.02
Fluoride	4		0.1
Lead	0.015	E200.8	0.01
Lithium	--	E200.7	
Mercury	0.002	E245.1	0.001
Molybdenum	--	E200.7	0.05
Radium 226		E903.0	
Radium 228		RA-05	
Radium 226 and 228 combined	5 pCi/L	A7500-RA	
Selenium	0.05	E200.8	0.01
Thallium	0.002	E200.8	0.01

When semiannual *detection monitoring* begins after October 2017, groundwater samples will be analyzed for Appendix III constituents only. In the event that a statistically significant increase over background levels has been detected for one or more of the constituents listed in Appendix III, the Site will enter *assessment monitoring*. During *assessment monitoring*, groundwater samples will be analyzed for all constituents in Appendix IV within the first 90 days of triggering the assessment monitoring program, and semi-annually thereafter. After two consecutive sampling events that demonstrate all constituents to be at or below background values, the Site monitoring program may return to *detection monitoring*.

### 3.0 FIELD SAMPLING PROCEDURES

The groundwater monitoring program involves collecting groundwater level measurements from the designated wells and piezometers and collecting groundwater samples from the designated wells. This section presents the specific procedures for performing these activities, including:

- groundwater monitoring locations,
- field measurement procedures and criteria,
- sampling methods,
- quality control sample protocols,
- sample container requirements,
- sample preservation methods,
- decontamination procedures, and
- documentation of sampling activities.

This section is intended to be a field manual, and provides field personnel with easy-to-use procedures and methods for consistently collecting quality, representative groundwater samples and measurements. Field personnel must understand and use these field sampling procedures (FSPs) during groundwater sampling events, consistently follow the specified procedures and protocols, and clearly document deviations from the FSPs, along with reasons for deviations.

Monitoring wells are listed in Table 2-1 along with their respective construction details. Borehole and well construction logs are provided in Appendix A. Appendix B contains field form templates for each monitoring event.

#### 3.1 GROUNDWATER LEVEL MONITORING

Groundwater level measurements are collected from all monitoring wells and piezometers at the beginning of each monitoring event, and prior to sampling. Groundwater levels are measured to the nearest 0.01 foot, from their respective well reference points (i.e., the top of the inner casing).



Groundwater level measurements are compared to the most recent measurements obtained for that well or piezometer. If the measurements differ by more than 0.5-foot, a second groundwater level measurement is collected for verification purposes.

Groundwater levels are measured using a decontaminated water level indicator. If multiple meters are used, the calibration of each meter is checked for accuracy. The following procedures are followed each time water levels are measured in a monitoring well:

1. Turn on water level meter. Depending on the condition of the water level meter, the sensitivity may have to be adjusted by turning the power switch dial to the desired sensitivity level. Typically, the water level meter works best adjusted to a low sensitivity.
2. Press the appropriate button to test the meter.
3. Clean the meter and/or confirm that the meter has been properly decontaminated.
4. Open/unlock well head.
5. Don a new pair of nitrile gloves.
6. Water level readings are measured relative to the surveyed mark on the top of the well's inner casing. If a mark is not present, measure from the northernmost top of well casing.
7. Lower the water level meter probe into the well. When the buzzer sounds and/or the light turns on, stop the probe's descent. Gently raise the probe until the buzzing stops. Gently lower the probe until the buzzing starts again and stop. The cable should be immediately next to the measuring mark from now until the final reading is measured. If the buzzer stays on, or is very weak, adjust the sensitivity.
8. Without changing the hold on the cable, raise the probe out of the water and retest the measurement.
9. Keep adjusting the hand location until two identical readings are noted. Identical readings will be the same to 0.01 of a foot.
10. If the numbers on the cable can be observed, read the measurement at the mark to the nearest 0.01 foot.
11. If the numbers on the cable cannot be observed, place fingers around the cable at the location where the buzzer sounds relative to the reference point, pull the cable out without moving your hand with respect to its location on the cable, and record the reading.
12. If the two readings are within 0.01 foot, record the depth to water reading on the appropriate form.
13. Remove the probe from the well. Take note where the cable becomes wet. The cable and probe below this point needs to be decontaminated.
14. Decontaminate the probe and two feet (or the appropriate length if more than two feet immersed in water column) of cable by immersing in an Alconox® solution followed by immersing in tap water and deionized water rinses, respectively.
15. Spool the remaining cable.
16. Secure the probe in the holder.

17. Turn off water level meter.
18. Commence sample collection procedures or close and lock the well.

### **3.2 GROUNDWATER QUALITY MONITORING**

Groundwater quality monitoring includes field and laboratory analyses. Only meters that were calibrated at the beginning of the work day are used to measure field water quality parameters, which include temperature, pH, dissolved oxygen (DO), oxidation-reduction potential (ORP), turbidity, and specific conductance (SC). Field water quality parameters are measured in a flow-through cell at regular intervals (typically every five minutes) during the low-flow process.

Samples analyzed by the contract laboratories are collected in new sample containers that are provided by the laboratory. Energy Laboratories, is the laboratory contracted by TMPA to provide analytical services.

#### **3.2.1 Groundwater Sample Collection Procedures**

The goal of groundwater sampling is to collect samples that are representative of in-situ groundwater conditions and to minimize changes in groundwater chemistry that would adversely affect analyte concentrations during sample collection and handling. To achieve this goal, groundwater samples are collected from the monitoring wells using U.S. Environmental Protection Agency's (EPA's) *Low Stress (low-flow) Purging and Sampling Procedure for the Collection of Groundwater Samples from Monitoring Wells* guidance (EQASOP-GW4), and summarized below.

Beginning with upgradient wells first, and progressing sequentially through wells with the lowest to highest contaminant concentrations, groundwater conditions are stabilized and samples collected in a consistent manner for each well. A variable speed electrical submersible pump or peristaltic pump is used to purge and collect groundwater samples from well.

The following procedures will be used when groundwater from monitoring wells, using the low-flow, minimal drawdown method:

1. Arrive at well location and start to fill out Well Sampling Record. Fill out: Date, Time, Well ID, and Sampler.
2. Put on new nitrile gloves.
3. Using a decontaminated water level meter, measure and record the depth to water from the measuring point to an accuracy of 0.01 foot. The measuring point is marked on the top of the inner casing.
4. If using a submersible pump, decontaminate the pump and connect and tighten the dedicated tubing to the submersible pump. Verify that safety lead and electrical connections to the submersible are tight and secure.

5. Lower the submersible pump to the sampling depth. If using a peristaltic pump, feed the dedicated tubing down to the sampling depth, then connect the tubing to the peristaltic pump.
6. Verify that the control box is at the lowest setting and start the pump..
7. Adjust the setting on the control box to the point where water is produced from the well.
8. Measure and record the pumping rate in milliliters per minute (ml/min) by collecting the discharged water in a beaker or graduated cylinder. Adjust the controller setting as needed so that the flow rate is between 100 and 500 ml/min.
9. Once maximum discharge rate is achieved without lowering water level more than 0.3 feet, record the final purge settings on the Well Sampling Record for use in future sampling events. The purge time starts when the settings are adjusted.
10. Collect purge water into five-gallon plastic containers as needed.
11. Connect the discharge line to the flow-through cell.
12. After the flow-through cell is connected and air bubbles evacuated to the extent possible, water quality parameters (pH, DO, ORP, SC, temperature, and turbidity) and depth to water (DTW) are measured and recorded at approximate five-minute intervals. The relative percent difference (RPD) and delta calculations are conducted and recorded between the readings.
13. When the well has been purged for 60 minutes or field water quality readings have stabilized, the well is ready to be sampled. The field parameters are considered stable when three consecutive field measurements meet the criteria listed in Table 3-1. If the well has been purged for 60 minutes and the field parameters have not stabilized, it is noted on the sampling log, and samples are collected from the well.
14. Collect a groundwater sample following the sample collection procedures in Section 3.2.
15. Stop the pump. Disconnect the pump from the power source. If a generator is used, turn off the generator.
16. Place the sample bottles into a plastic bag and into a cooler with ice.
17. Disconnect the tubing from the submersible/peristaltic pump, secure the dedicated tubing in a clean, clearly labeled storage bag and secure the well cover. (The storage bag is placed in the on-site storeroom at the end of the day).
18. Decontaminate the water level meter and submersible pump (if used) following the procedures indicated in Section 3.8.
19. Pack up the equipment and mobilize to the next well.
20. The purge and decontamination waters can be discharged to the ground near the well or Ash Ponds or Scrubber Sludge Pond.

The submersible pump (if used) and dedicated tubing are positioned at the same depth (approximately halfway through the screened interval) in each well for each sampling event. The purge rates for each well typically are similar during successive sampling events. The purge rate

for the low-flow method wells initially can be set to the rate used in previous events and adjusted as needed based on current groundwater conditions.

### 3.2.2 Field Parameter Measurements and Stabilization

Field water quality data are recorded during well purging to determine when groundwater conditions in the well have stabilized, and representative formation water is being sampled. As stated above, field parameters are measured in a flow-through cell at regular intervals (typically every five minutes) during the low-flow purging process, and purging continues until the field parameters have stabilized based on the criteria summarized in Table 3-1, or until the maximum purge volume/time is met.

<b>Table 3-1. Field Parameter Stabilization Criteria for Monitor Well Purging and Sampling</b>	
<b>Parameter</b>	<b>Low-Flow Method</b>
pH	+/- 0.1 S.U.
Conductivity	+/- 3%
Temperature	+/- 3%
Dissolved Oxygen	+/- 10% or +/- 0.1 mg/l if <2.0
ORP	+/- 10% or +/- 10 mV if < 100
Turbidity	<10 NTU or +/- 10%
Drawdown	<0.3'
Pumping rate	100-500 ml/min
Volume	No Criteria
Time	Maximum of 60 min

Notes: All percentages are relative percent difference.

The stabilization criteria are also listed on the well sampling forms in Appendix B.

### 3.2.3 Sample Collection

When the stabilization criteria are met, a groundwater sample is collected. Groundwater samples are collected from the pump discharge line directly into laboratory-supplied containers appropriate for the specific analysis being conducted. Specific procedures for collecting groundwater samples include the following:

1. Fill out the sample bottle labels using a pen with black waterproof ink. Place the preservative provided by the lab in the appropriate bottle(s).
2. Don new nitrile gloves.
3. Disconnect the pump's discharge line from the flow-through cell.

4. Fill the sample bottles being careful not to overfill bottles with preservative.
5. Stop the pump.
6. Place the bottles into a cooler with ice.

Other general procedures that are followed during sampling include:

- Avoid rinsing the sample bottles before filling.
- Collect water sample from the pump's discharge line directly into laboratory-supplied containers appropriate for the specific analysis being conducted.
- Open only one sample container at a time. Immediately replace the container's cap and make sure the label is completed before starting to fill the next bottle.
- Minimize the potential for contamination to sample containers and equipment by sampling up wind and/or removing contaminants before opening containers. Common contaminants may include dust or other particulate matter.
- Immediately put the cap on each bottle after filling it.
- Place filled sample bottle into an iced cooler (except for radiochemical analysis) and enter sample information onto the appropriate chain of custody (COC) forms.

### 3.2.4 Sample Containers, Preservation, and Holding Times

Table 3-2 lists the number of sample bottles, the laboratory analyte(s), the type and size of the sample containers, the preservatives, and holding times. All samples are collected into new bottles supplied by the laboratory. If preservatives are added into the sample containers by the laboratory, that information is clearly marked on the container.

Qty. <sup>(1)</sup>	Analyte(s)	Type-Size	Preservative	Method	Holding Time
1	Appendix III Constituents <sup>(2)</sup>	Polyethylene-1 L	None	No filter	28 days
1	Appendix IV Metals <sup>(3)</sup>	Polyethylene-500 ml (alternate - 16 oz.)	Nitric Acid to pH < 2	No filter	28 days for mercury, 6 months for others
1	Appendix IV Radium 226 and 228	Polyethylene-2L (alternate - 0.5 gal.)	Hydrochloric Acid to pH < 2	No filter	28 days

- Notes: (1) Number of sample bottles filled for analyte(s).  
(2)pH, total dissolved solids, boron, cadmium, chloride, sulfate, fluoride,  
(3)Antimony, arsenic, barium, beryllium, cadmium, chromium, cobalt, lead, lithium,  
mercury, molybdenum, selenium, thallium.

"L"=liter

"ml"=milliliters

### 3.3 DOCUMENTATION OF FIELD ACTIVITIES

All field activities, including daily activities, sample locations and identification numbers, and significant observations or events, are documented by field staff on the appropriate forms. Specific forms for water level monitoring, equipment calibration, and groundwater sampling are included in Appendix B. The data are intended to record events in sufficient detail to allow personnel, at a later date, to reconstruct events that transpired during the life of the project. Entries are written in black indelible ink to allow preservation of information. The general documentation requirements are summarized as follows:

1. Entries will be legible.
2. Entries will be written in indelible black ink.
3. Mistakes will be corrected by drawing a single line through the error. Corrections will be initialed. No entries will be obliterated for any reason.
4. The tops of pages will be numbered sequentially and dated. The sampler will initial and date the bottom of each page and sign the last page for each day.
5. There will be no pages left blank.
6. Opinion or subjective material will not be entered into the logbook.

Each day, the following data are recorded in the logbook:

1. Project name and date.
2. Daily objectives and task progress throughout the day.
3. Weather (temperature, cloudiness, barometric pressure, wind).
4. Water quality and turbidity meters used (type, model).
5. Person calibrating meter(s).
6. Calibration results (buffers used with manufacturer, lot numbers, and expiration dates).
7. Problems calibrating meters.
8. Objective status at the end of the day, and issues encountered.

At each well, the following data is recorded in the logbook:

1. Well name and arrival time.
2. Person(s) sampling.
3. Purging method (low-flow or well volume).
4. QA/QC samples collected and the sample designation.
5. Samples preservation (ice, acid preservative).
6. Equipment decontamination procedures.
7. Decontamination/purge water disposal.
8. Comments (difficulties, questionable data, deviations from this plan, etc.).
9. Problems with field meters.
10. Visitors (name, title, organization).

### **3.4 SAMPLE IDENTIFICATION, DOCUMENTATION, AND CUSTODY**

Collected samples are labeled in water-proof ink with the following information:

- sample name,
- date and time of collection,
- name or initials of person collecting the sample, and
- analyte list.

Similar information is also entered on the COC form, which remains with the respective collected sample through delivery to the analytical laboratory. Samplers maintain proper custody of their respective samples until delivery to the laboratory, or the samples are relinquished to another party. A sample is considered to be under a person's custody if:

- the sample is in the person's physical possession;
- the sample is in view of the person after that person has taken possession of the sample;
- the sample is secured by that person so that no individual can tamper with the sample; or
- the sample is secured by that person in an area that is restricted to authorized personnel.

Completed COC forms are delivered with the samples to the analytical laboratory. Each COC form must match the samples included in the associated cooler. The COC forms include the following information:

- Project name.
- Unique sample identification number.
- Unique COC number.
- Sample collection date and time.
- Sample matrix.
- Number and type of containers submitted.

- Preservation method, if applicable.
- Analyses requested for each sample.
- Special handling or analysis requirements.
- Courier shipment tracking number.
- Dated signature of the person collecting the samples.
- Dated signature(s) of persons, other than the sampler, involved in the delivery of the samples to the laboratory.
- Dated signature of the laboratory acknowledging receipt of the collected samples.

The COC form is filled out and signed in black indelible ink. The COC number and the date and time of delivery to the laboratory are noted in the field logbook. A copy of the COC form is delivered to and retained by the Project Manager.

### **3.5 SAMPLE PACKING AND TRANSPORT**

Once collected, groundwater samples are packed for transport to the analytical laboratory. Care should be taken in packing the groundwater samples so that there is no damage to sample containers during transport to the contract laboratory. Samples are delivered to:

Energy Laboratories  
1120 South 27<sup>th</sup> Street  
Billings, Montana 59101  
(406) 252-6325

Custody seals will not be required on the coolers if they are turned over directly to laboratory personnel at the time of delivery. Coolers delivered to the laboratory after hours will be placed in the designated receiving storage locker and custody seals placed on the right and left front and back sides across the gap between the lid and the cooler. The storage locker will be locked and the laboratory notified that coolers have been placed in the after-hours storage locker.

### **3.6 FIELD EQUIPMENT CALIBRATION**

The field water quality meters are calibrated following the manufacturer's instructions. Except for temperature, pH, SC, DO, ORP, and turbidity are calibrated at the start of each day, and checked immediately after calibration, and at any time the meter is believed to be operating poorly. Calibration readings are recorded on the field calibration form, included in Appendix B. A meter is recalibrated when the reading is not within +/-10% of the standard solution or +/-0.20 pH units of the buffer solution. If the meter cannot be recalibrated, it is not used, and is sent to the rental supplier for repair.

At the end of each day of sampling, potential drift in parameter readings is evaluated by measuring standards for each parameter. The drift readings also are recorded on the field calibration form. Acceptable performance of the meter(s) is indicated by a drift of +/- 0.20 standard units for pH and +/- 10% for the remaining calibrated parameters.



### **3.7 SAMPLE DOCUMENTATION AND RECORDS**

Field activities, including daily activities, sample locations and identification numbers, and any significant observations or events, are described in detail on the appropriate forms and/or in a field notebook. The activities and details, complete with time tags, are also written in the bound field logbook. There are individual forms for water level monitoring, equipment calibration, and groundwater sampling. Copies of these forms are included in Appendix B. The data are intended to record events in sufficient detail to allow personnel, at a later date, to reconstruct events that transpired during the life of the project. Entries are written in black indelible ink to allow preservation of data. Mistakes are corrected by drawing a single line through the error and the author initialing next to the deleted error. No entries will be obliterated for any reason.

### **3.8 EQUIPMENT DECONTAMINATION**

Water level monitoring and non-dedicated groundwater sampling equipment that come in contact with groundwater are cleaned prior to use and between sampling locations. The non-dedicated submersible pump is decontaminated by pumping a series of solutions through the pump. The solutions are pumped in the following order: non-phosphate detergent (Alconox®), tap water, and deionized water. The last two feet of the water level meter cable is decontaminated by immersion in a non-phosphate detergent solution followed by immersion in tap water and deionized water rinses, respectively. After decontamination, equipment is stored and/or transported under clean conditions. Typically, equipment is stored in a clean plastic bag until reuse.

### **3.9 HANDLING AND DISPOSITION OF INVESTIGATION-DERIVED WASTES**

Due to the low levels of target parameters, purge water can be discharged to the ground in the vicinity of the well. Alternately, purge water can be placed in the Ash Pond or Scrubber Sludge Pond.

## **4.0 QUALITY ASSURANCE/QUALITY CONTROL**

### **4.1 STANDARD OPERATING PROCEDURES**

The groundwater sampling procedures in Section 3.0 will be followed when collecting groundwater samples and measuring water levels and field parameters. The use of these standard operating procedures is meant to ensure consistency across multiple sampling events and possibly different personnel.

### **4.2 SAMPLE ANALYSIS VALIDATION**

The type and reliability of methods used to analyze samples is important to ensure data quality. This section describes the collection of Quality Assurance/Quality Control (QA/QC) samples and the data review procedures that will be followed to ensure acceptable data.

#### **4.2.1 Quality Assurance and Quality Control Samples**

Samples are collected at regular intervals for QA/QC purposes. These samples include duplicate, field blank, and/or equipment rinse samples. The designations given to QA/QC samples and the associated original samples are documented on the sampling logs and in the logbook.

Duplicate samples are used to compare results from two separate samples taken from the same location at a rate of one duplicate per ten samples (or less). For each duplicate, a second set of bottles is filled following the same procedures as used for the original sample. The duplicate and original sample bottles are filled by alternating the discharge between the bottles after each one-third of the bottle is filled. Duplicate samples are designated by adding the suffix “-FD” to the well name from which the duplicate was collected (e.g., a duplicate sample from SFL MW-3 is designated as SFL MW-3 -FD). Wells selected for duplicate analysis change with each sampling event and are identified on the sampling log.

Field blanks and equipment rinse blanks are collected during each sampling event. Blank samples are used to evaluate cross-contamination. Each blank sample is a full bottle set with a unique sample designation. Field blanks are designated as “FB”, whereas equipment rinse blanks are designated as “EQ”. Each blank is sequentially numbered in the order collected starting with “01”. The sample bottles are filled with deionized (DI) water in the same manner as the original sample. Field blanks are collected at a rate of one blank for every 20 samples (or less). Equipment rinse blanks are collected when non-dedicated sampling equipment is used, at a rate of one sample per workday. Once sampling equipment has been decontaminated, DI water is pumped through the equipment into the appropriate sample bottles. The well locations from where field and equipment rinse blanks are collected are documented on the Well Sampling Record and the field logbook.

#### **4.2.2 Data Review Procedures**

To ensure quality data collection and compliance with CCR data quality regulations, a data review will be conducted for each sampling event. The contract laboratory will complete a review of the data in accordance with its internal laboratory guidelines and the applicable analytical methods used during sample analysis. Each data package from the laboratory will include a QC summary report.

A data usability review will be completed by Amec Foster Wheeler for each sampling event. A Data Usability Summary (DUS) will be prepared in accordance with TCEQ RG-366/TRRP-13. The DUS procedures were developed by the TCEQ for use in its Texas Risk Reduction Program but provide a common, known methodology for evaluating data usability. A DUS report will be prepared and included in the project file.

**Table 2-1  
Well Construction Details  
TMPA Gibbons Creek Steam Electric Station**

Well ID	Northing <sup>1</sup>	Easting <sup>1</sup>	Land Surface Elevation (ft. amsl)	Measuring Point Elevation (ft. amsl)	Total Well Depth (ft. below TOC)	Total Well Depth (ft. bgs)	Total Borehole Depth (ft. bgs)	Total Depth (elevation)	Screen Interval (ft. bgs)		Screen Interval (elevation)	
									Top	Bottom	Top	Bottom
AP MW-1D	10213589.808	3635630.942	269.02	272.04	43.0	40.0	40.0	229.0	34.5	39.5	234.5	229.5
AP MW-3	10213665.476	3635026.590	271.46	274.68	43.4	40.2	40.0	231.3	34.5	39.5	237.0	232.0
AP MW-4	10212415.597	3635562.990	270.93	274.16	52.8	49.6	50.0	221.4	44.5	49.5	226.4	221.4
AP MW-5	10212901.968	3635577.940	271.16	274.13	43.1	40.1	40.0	231.0	30.5	35.5	240.7	235.7
AP MW-6	10212689.394	3634726.766	274.74	277.95	48.1	44.9	50.0	229.9	41.0	46.0	233.7	228.7
AP PZ-1 <sup>2</sup>	10214173.721	3634278.958	262.70	265.67	29.4	26.4	35.0	236.3	21.0	26.0	241.7	236.7
AP PZ-2 <sup>2</sup>	10214308.029	3634847.514	271.71	274.91	43.2	40.0	40.0	231.7	34.5	39.5	237.2	232.2
AP PZ-3 <sup>2</sup>	10213822.938	3635414.358	255.76	259.11	43.1	39.7	40.0	216.0	34.5	39.5	221.3	216.3
AP PZ-4 <sup>2</sup>	10211826.931	3634752.131	271.39	273.65	45.3	43.0	45.0	228.4	38.5	43.5	232.9	227.9
SSP MW-2	10212007.735	3633835.274	280.62	283.66	46.9	43.9	45.0	236.8	38.5	43.5	242.1	237.1
SSP MW-3	10211581.588	3633889.744	280.95	283.97	48.2	45.2	45.0	235.8	39.5	44.5	241.5	236.5
SSP MW-4	10211577.225	3634198.516	280.86	283.86	51.5	48.5	50.0	232.3	43.0	48.0	237.9	232.9
SSP/AP MW-1	10212432.016	3634290.363	269.33	272.53	43.2	40.0	40.0	229.3	29.5	39.5	239.8	229.8
SFL MW-2	10220908.018	3636738.712	265.69	268.31	23.6	21.0	50.0	244.7	16.0	21.0	249.7	244.7
SFL MW-3	10220174.555	3637846.961	271.65	275.00	28.2	24.9	25.0	246.8	19.5	24.5	252.2	247.2
SFL MW-4	10220291.840	3637261.610	266.46	269.53	42.7	39.6	40.0	226.8	34.5	39.5	232.0	227.0
SFL MW-5	10221191.234	3636721.834	273.33	276.25	24.3	21.4	25.0	251.9	16.0	21.0	257.3	252.3
SFL MW-6	10221819.634	3636700.033	283.49	286.66	23.1	19.9	20.0	263.6	14.5	19.5	269.0	264.0
SFL MW-7	10220517.925	3638408.836	264.83	264.63	58.1	58.3	55.0	206.5	50.0	55.0	214.8	209.8
MNW-11 <sup>2</sup>	10220909.018	3635624.897	268.12	267.95	47.3	47.5	48.0	220.7	42.5	47.5	225.7	220.7
MNW-15	10220778.128	3638974.095	257.536	257.331	27.0	27.2	27.7	230.3	22.2	27.2	235.3	230.3
MNW-16 <sup>2</sup>	10222188.729	3635593.380	263.333	263.191	40.4	40.5	41.0	222.8	35.5	40.5	227.8	222.8
MNW-17 <sup>2</sup>	10223663.517	3637468.447	293.864	293.724	50.2	50.4	50.9	243.5	45.4	50.4	248.5	243.5
MNW-18	10224118.439	3639397.902	270.912	270.755	51.0	51.2	51.7	219.7	46.2	51.2	224.7	219.7

<sup>1</sup>Datum - NAD 83 (Conus)

<sup>2</sup>Water levels only, not used in groundwater quality monitoring

## FIGURES

---




**Amec Foster Wheeler  
Environment & Infrastructure**  
3755 S. Capital of Texas Highway, Ste. 375  
Phone: (512) 795-0360 Fax: (512) 795-8423



Approximate Scale in Miles

Source: Google Earth




**CCR UNITS**  
Texas Municipal Power Agency  
Gibbons Creek Steam Electric Station  
Grimes County, Texas




Project No. 6706150060  
Date: 10/12/2017



Figure 1.1

Plot Date: 10/10/17 - 5:30pm. Plotted by: susan.l.brown  
 Drawing Path: P:\1670615 Projects\6706150060 - TMPPA - Gibbons Creek Mine\5000 CCR GW Monitoring\Figures - Drawing Name: Figure 1 Potentiometric Map\_Landfill.dwg



**LEGEND**

-  Amec Foster Wheeler Monitoring Well
-  Black and Veatch Monitoring Wells
-  Well Used for Groundwater Level Monitoring Only




SOURCE:  
 POTENTIOMETRIC SURFACE ELEVATION AND BASE MAP, ERM  
 GOOGLE EARTH PRO




**SITE F LANDFILL**  
 Texas Municipal Power Agency  
 Gibbons Creek Steam Electric Station  
 Grimes County, Texas

Project No. 6706150060	<b>Figure 2-1</b>
Date 10/2/2017	



**LEGEND**

-  Monitoring Well
-  Piezometer
-  Well Used for Groundwater Level Monitoring Only



**SCRUBBER SLUDGE POND  
AND ASH POND**  
Texas Municipal Power Agency  
Gibbons Creek Steam Electric Station  
Grimes County, Texas

Project No.: 6706150060  
Date: 10/10/2017

Figure 2.2

Plot Date: 10/10/17 - 5:14pm, Plotted by: susan.l.brown  
Drawing Path: P:\1 670615 Projects\6706150060 - TMIPA - Gibbons Creek Mine\5500 CCR GW Monitoring\Figures, Drawing Name: Figure 2 Potentiometric Map\_Ponds\_DWG

Basemap modified from Potentiometric Surface Elevation and Base Map, ERM, Google Earth Pro

**APPENDIX A**

---

Borehole Logs and Well Installation Diagrams



PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. AP MW-1D</b>	
BORING LOCATION: <b>Northeast Corner of Ash Ponds</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/24/16</b>	DATE FINISHED: <b>5/24/16</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>40.0</b>	SCREEN INTERVAL (ft.): <b>34.5'-39.5</b>
DRILLING EQUIPMENT: <b>8 5/8" OD HSA Truck Mounded Rig</b>		DEPTH TO WATER ATD: <b>35</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot				
					Sandy clay fill to 4.5'	
5					Slightly SANDY CLAY (CH): light yellowish-brown, dry, hard, trace calcium carbonate nodules, fine-grained sand to 5' SANDY CLAY (CH): light yellowish-brown, slightly moist, hard, fine-grained sand, trace pebbles	
					Lignite, dark brown, slightly moist, firm 7'-8.5'	
10					SANDY CLAY (CL): light olive brown, moist, very stiff, fine-grained sand, trace of small gravel size nodules, minor ferrous staining SANDY CLAY (CL): light olive brown, brown lenses, dry, fine-grained sand, stiff	
					SILTY SAND (SM): dark gray, very moist	
15					CLAYEY SAND (SC): light olive brown, moist, very stiff, fine-grained sand CLAYEY SAND (SC): light olive brown, moist, firm, fine-grained sand SILTY SAND (SM): light olive brown, wet, loose, fine-grained at 16'	
20					SILTY SAND (SM): light olive brown, wet, loose, fine-grained sand	
25						

WELL3

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						1" hard shaley sand lenses at 25.5' SILTY SAND (SM): light olive brown, wet, loose, fine-grained, one ferrous stained sand lens  at 16' SILTY SAND (SM): light olive brown, wet, loose, fine-grained sand 2" sandstone lens, hard at 31.5'  4" sandstone lens, hard at 33'  3" sandstone lens, ferrous staining, hard, blocky at 34.25' SILTY SAND (SM): light olive brown, wet, loose, fine-grained sand  SILTY SAND (SM): light olive brown with very thin lignite lenses  2" hard sandstone layer at 40'	<p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
40						Total Depth = 40'	
45							
50							
55							

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. AP-MW-3</b>	
BORING LOCATION: <b>Northeast Corner of Ash Ponds</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/25/16</b>	DATE FINISHED: <b>5/25/16</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>40.0</b>	SCREEN INTERVAL (ft.): <b>34.5'-39.5</b>
DRILLING EQUIPMENT: <b>8 5/8" OD HSA Truck Mounded Rig</b>		DEPTH TO WATER ATD: <b>20</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot			
5					SANDY CLAY with gravel (CH): brown, moist, firm, fine-grained sand, few small gravel, (fill)	
					SANDY CLAY with gravel (CL): brown and reddish-brown, moist, very stiff, fine-grained sand, few small gravel, few clay clasts, 3-4' layers (fill)	
10					SANDY CLAY with gravel (CL): brown mottled, moist, very stiff, fine-grained sand, trace of small gravel (fill)	
15					SILTY SAND (SM): light olive brown, moist, firm, fine-grained sand	
					SILTY SAND (SM): light olive brown, moist, fine-grained sand	
20					SILTY SAND (SM): light olive brown, wet, fine-grained sand	
25						

WELL3

### Log of Well No. AP-MW-3 (cont'd)

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						SILTY SAND (SM): light olive brown, wet, fine-grained sand  - siltstone interbedded with loose sand 27.5'-28.75'  Siltstone, light olive gray, dry, hard at 28.75' and 29.5'  SILTY SAND (SM): light olive brown, moist, fine-grained sand SILTY SAND (SM): light olive brown, wet, fine-grained sand	<p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
35						SILTY SAND (SM): light olive brown, wet, fine-grained sand	
40						Total Depth = 40'	
45							
50							
55							

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. AP MW-4</b>	
BORING LOCATION: <b>East of Ash Ponds</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>6/1/16</b>	DATE FINISHED: <b>6/1/16</b>
DRILLING METHOD: <b>CME 75 HSA</b>		TOTAL DEPTH (ft.): <b>50.0</b>	SCREEN INTERVAL (ft.): <b>44.5'-49.5'</b>
DRILLING EQUIPMENT: <b>CME 75 8 5/8" OD HSA</b>		DEPTH TO WATER ATD: <b>48</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot				
5					SANDY CLAY (CL): dark yellowish-brown, brown, moist, stiff, fine-grained sand, sand fill to 3.5'	<p>2" Diameter PVC</p> <p>Grout</p>
				SANDY CLAY (CH): brown, moist, stiff, fine-grained sand		
				SANDY CLAY (CH): brown, mottled, moist, firm, clay clasts, fine-grained sand		
10				SANDY CLAY (CL): yellowish-brown, moist, firm, fine-grained sand, few pebbles		
15				SANDY CLAY (CL): olive brown and yellowish-brown, moist, stiff, 3" lignite lense at 14.75'		
20				SANDY CLAY (CL): yellowish-brown, moist, stiff, fine-grained sand, bedding planes, yellow and black streaks		
25				SANDY CLAY (CL): yellowish-brown, moist, stiff, fine-grained sand, bedding planes		
				Lignite, black, moist, firm 23.5'-25'		

WELL3

### Log of Well No. AP MW-4 (cont'd)

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						SANDY CLAY (CH): yellowish-brown, moist, soft, fine-grained sand, discontinuous lignite lenses	
						Lignite, black, moist, firm 26.5'-30'	
35						SANDY CLAY (CH): olive-brown, moist, fine-grained sand, stiff	
						Perched water at 32'	
40						Lignite, black, dry, stiff 34'-37.5'	
						Interbedded silty sand and sandy clay, thin bedded (1/4" - 1/2"), olive brown, sandy clay, gray silty sand, dry, stiff, fine-grained sand Lignite, black, dry, hard, 6" CLAY (CL): black, dry, hard, blocky, some interbedded black lignite	
45						SANDY CLAY (CL): black, dry, hard, fine-grained sand, platty	
						SILTY SAND (SM): dark olive brown, wet, loose, bedding planes, fine-grained sand	
50						Total Depth =50'	
55							

WELL3

PROJECT: TMPA Gibbons Creek Plant Carlos, Texas		<b>Log of Well No. AP MW-5</b>	
BORING LOCATION: East Center of Ash Ponds		GROUND SURFACE ELEVATION AND DATUM: NA	
DRILLING CONTRACTOR: Best Drilling		DATE STARTED: 6/1/16	DATE FINISHED: 6/1/16
DRILLING METHOD: CME 75 HSA		TOTAL DEPTH (ft.): 40.0	SCREEN INTERVAL (ft.): 30.5'-35.5'
DRILLING EQUIPMENT: CME 75 8 5/8" OD HSA		DEPTH TO WATER ATD: 29	CASING:
SAMPLING METHOD: 5' x 4" Core Barrel		LOGGED BY: Daniel B. Haug, P.G.	
HAMMER WEIGHT: NA	DROP: NA	RESPONSIBLE PROFESSIONAL: Daniel B. Haug, P.G.	REG. NO. 1773

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation: NA	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot				
					Sand and clay fill to 2.5'	
5					SANDY CLAY (CH): yellowish-brown, moist, firm to hard, fine-grained sand, some mottling  SANDY CLAY (CH): light yellowish-brown, moist, stiff, trace of small gravel, fine-grained sand	2" Diameter PVC
10					SANDY CLAY (CL): reddish-brown then light yellowish-brown, (14'-15'), moist, stiff, sand lense at 14.5', fine-grained sand	Grout
15					SANDY CLAY (CH): yellowish-brown, moist, firm, fine-grained sand  CLAYEY SAND (SC): yellowish-brown, wet, firm, fine-grained sand, few gravel	
20					SANDY CLAY (CL): yellowish-brown, moist, firm, fine-grained sand, clay clasts SANDY CLAY (CH): reddish-brown mottled with grayish-brown, moist, firm, fine-grained sand  SANDY CLAY (CH): brown mottled with few reddish-brown streaks, moist, fine-grained sand, few pebbles	
25						

WELL3

### Log of Well No. AP MW-5 (cont'd)

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
						SANDY CLAY (CH): brown, moist, fine-grained sand to small gravel	<p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
30					CLAYEY SAND (SC): brown, wet, firm, fine- to coarse-grained sand		
					SANDY CLAY (CL): light yellowish-brown, moist, stiff, fine-grained sand, ferrous staining		
35					SANDY CLAY (CL): light yellowish-brown, very moist to wet, medium-grained sand		
					CLAYEY SILTY SAND (SC-SM): dark greenish gray, slightly moist, fine-grained sand		
40					Total Depth = 40'		
45							
50							
55							






WELL3



PROJECT: TMPA Gibbons Creek Plant Carlos, Texas		<b>Log of Well No. AP MW-6</b>	
BORING LOCATION: West Side of Ash Ponds		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: Tolunay-Wong		DATE STARTED: 5/3/17	DATE FINISHED: 5/5/17
DRILLING METHOD: HSA with Continuous Core Borell		TOTAL DEPTH (ft.): 50.0	SCREEN INTERVAL (ft.): 41'-46'
DRILLING EQUIPMENT: CME 75		DEPTH TO WATER ATD:	CASING:
SAMPLING METHOD: 5' x 4.25" OD Core Barrel		LOGGED BY: Daniel B. Haug, P.G.	
HAMMER WEIGHT: NA	DROP: NA	RESPONSIBLE PROFESSIONAL: Daniel B. Haug, P.G.	REG. NO. 1773

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot			
					Grass at the surface, gravel, sand and clay material to 4.25' (probable fill)	
5				0.3	SANDY CLAY (CL): yellowish-brown, moist, stiff, ferrous nodules, trace of caliche, fine-grained sand	2" Schedule 40 PVC Riser
				0.1	SILT (ML) with lignite: reddish-brown, dry, firm, very little recovery	
10					CLAY (CL): reddish-brown, slightly moist, firm Lignite with clay, dark red, slightly moist, firm	Bentonite Grout
				0.1	SANDY CLAY (CL): yellowish-brown, dry, firm, very fine-grained sand  2" lignite seam, dark reddish-brown, slightly moist, soft	
15				1.8	CLAY (CH): yellowish-brown, slightly moist to moist, stiff, ferrous staining Interbedded CLAY and LIGNITE (0-CL): black to reddish-brown, dry, firm to hard 1" cemented lenses with gypsum	
20				2.1	LIGNITE (0) with hard lenses of cemented clay and silt with organics: dark brown, dry, hard	
25					SANDY CLAY (CL): dark brown, dry, stiff, very fine-grained sand, numerous thin very fine-grained sand partings, laminated	

WELL3


DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot	Foot			
30					2.5	Interbedded SAND and LIGNITE (SP-0): sand - olive gray, lignite - black, very moist to wet, mostly sand, fine-grained sand	
						LIGNITE (0): black, dry, hard - Lignite to 30.25'	
35					4.3	CLAY (CL): light gray, slightly moist, hard	
						CLAYEY SAND (SC): very dark grayish-brown, dry, dense, very fine-grained sand, lignite fragments	
40					4.9	CLAYEY SAND (SC): olive gray, slightly moist to moist, dense, fine-grained sand, weakly cemented, laminated	
						Slightly CLAYEY SAND (SC): olive gray, moist to very moist, 42.5'-43' wet, moist below 43' and silty, medium dense, very fine- to fine grained sand	
45					4.4		
						Very slightly CLAYEY SILTY SAND (SM): olive gray, moist, dense, fine-grained sand, trace of lignite lenses	
50					0.6	- Sulfur smell	
						Total Depth = 50"	
55							

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. AP PZ-1</b>	
BORING LOCATION: <b>West of Limestone Storage Building</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/24/16</b>	DATE FINISHED: <b>5/24/16</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>35.0</b>	SCREEN INTERVAL (ft.): <b>21'-26'</b>
DRILLING EQUIPMENT: <b>8 5/8" OD HSA Truck Mounded Rig</b>		DEPTH TO WATER ATD: <b>21</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot				
					6" ash	
					Sandy clay with few small gravel fill to 2"	
5					SANDY CLAY (CH): yellowish-brown, moist, stiff, fine- to coarse-grained sand	2" Diameter PVC
					CLAYEY SAND (SC): light yellowish-brown, moist, stiff, fine-grained sand	Grout
10					0.5" sandstone lense at 9.25'	
					CLAYEY SAND (SC): light yellowish-brown, slightly moist, stiff, fine-grained sand	
					sandstone nodules and 0.5" sand lense at 12'-12.5'	
					- trace of ferrous staining	
15					- interbedded sand and sandy clay	
					CLAYEY SAND and SAND (SP, SC) olive-gray, dry to moist, loose to firm	
					CLAY (CL): brown, dry, hard, with interbedded sand and clay	Bentonite
					SILTY SAND (SM): brown, dry, loose to firm, fine-grained sand, clay lenses	
20					CLAY (CL): yellowish-brown, dry, hard, thin fine-grained sand lenses, trace of pebbles	20/40 Grade Silica Sand
					CLAYEY SAND with sandstone lenses, brown, wet, dense, fine-grained to small gravels size	
					SANDY CLAY (CL): brown, dry, hard, fine-grained sand lamina	Schedule 40 PVC 0.010 Slot Screen
25					SILTY SAND (SM): olive gray, moist, loose to firm, fine-grained sand	

WELL3

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						<p>SILTY SAND (SM): light olive gray, wet, hard, fine-grained sand, very thin lignite seams</p> <p>CLAY (CH): olive, dry, hard, blocky</p> <p>CLAY (CH): olive, dry, hard, blocky</p>	 <p>6" End Cap</p> <p>20/40 Grade Silica Sand</p>
35						Total Depth = 35'	
40							
45							
50							
55							

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. AP PZ-2</b>	
BORING LOCATION: <b>North of Fly Ash Silos</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/23/16</b>	DATE FINISHED: <b>5/24/16</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>40.0</b>	SCREEN INTERVAL (ft.): <b>34'-39'</b>
DRILLING EQUIPMENT: <b>8 5/8" OD HSA 2" Rods</b>		DEPTH TO WATER ATD: <b>39</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot				
5					SILTY SAND (SM): dark gray, slightly moist, loose, fine- to coarse-grained sand, roots, fly ash  SILTY SANDY CLAY (CH): brown, moist, firm, fine- to coarse-grained sand  SILTY SANDY CLAY (CL): brown, moist, firm, fine- to coarse-grained sand, increasing sand content  SANDY CLAY (CH): yellowish-brown, moist, soft, fine- to coarse-grained	<p>2" Diameter PVC</p> <p>Grout</p>
10					SILTY SANDY CLAY (CH): yellowish-brown, moist, hard, fine-grained sand, ferrous staining - lignite seam 9'-9.5'  CLAYEY SAND (SC): light olive brown, dry, dense, fine- to medium-grained sand, wood fragments  SILTY CLAYEY SAND (SC): light yellowish-brown, moist, firm, fine-grained sand	
15					SANDY CLAY (CH): yellowish-brown, dry, hard, fine-grained sand, lignite seam (thin)  CLAYEY SILTY SAND (SM): gray, wet, firm, fine-grained sand	
20					SANDY CLAY (CH): light yellowish-brown, dry, hard, layered, fine-grained sand  SILTY SANDY CLAY (CL): light olive brown, dry with few moist intervals, hard to very stiff, fine-grained sand, drier after 22'	
25						

WELL3





DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						<p>SILTY SAND (SM): light olive brown, very moist, fine-grained sand, soft</p> <p>Slightly SANDY CLAY (CH): brown, dry, hard, fine-grained sand lenses</p> <p>- increased sand content with depth</p>	<p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
						<p>SILTY SAND (SM): light olive brown, moist, fine-grained sand, firm</p> <p>CLAYEY SILTY SAND (SM): light olive gray, very moist, firm, 1/4" lignite seams, fine-grained sand</p>	
35						<p>SANDY CLAY (CL): light olive brown, moist to dry, hard, fine-grained sand, very hard lenses, organics (wood) in sandstone</p>	
40						<p>SILTY SAND (SM): light olive brown, wet to 39', tan lignite lenses (1/4"), fine-grained sand</p>	
						<p>CLAY (CH): brown, moist, hard</p> <p>Total Depth = 40'</p>	
45							
50							
55							

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. AP PZ-3</b>	
BORING LOCATION: <b>North of Ash Ponds</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/25/16</b>	DATE FINISHED: <b>5/25/16</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>40.0</b>	SCREEN INTERVAL (ft.): <b>34.5'-39.5</b>
DRILLING EQUIPMENT: <b>8 5/8" OD HSA Truck Mounded Rig</b>		DEPTH TO WATER ATD: <b>25</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot			
5					SANDY CLAY with Gravel (CH): yellowish-brown, moist, very stiff, fine-grained sand, few small gravel, probably fill	
					SANDY CLAY (CL): olive brown, moist, very stiff, fine-grained sand	
					SANDY CLAY (CL): light olive brown, slightly moist to moist at 9', firm, layered, fine-grained sand	
10					SANDY CLAY (CL): light olive brown, moist to wet above underlying clay, fine-grained sand, loose	
					CLAY (CH): light olive brown, dry, blocky, hard, layered	
					SILTY SAND (SM): light olive brown, wet, fine-grained sand	
15						
					SILTY SAND (SM): light olive brown, wet, fine-grained sand, layered	
20						
					SILTY SAND (SM): light olive brown, wet, fine-grained sand, layered	
25					- interbedded sand and siltstone	

WELL3

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
						<p>SILTY SAND (SM): light olive brown, wet, fine-grained sand, hard siltstone at 28.75' to 29' and 1" lense at 27.5' ferrous staining around siltstone lenses</p>	
30						<p>SILTY SAND (SM): light olive brown, wet, loose, fine-grained sand            Sandstone, light to olive brown, wet, hard, platy 32.5'-33'</p>	 <p>Bentonite</p>
35						<p>SILTY SAND (SM): light olive brown, wet, loose, fine-grained sand            Sandstone, pale yellow, wet, hard, platy 34'-34.5'</p>	 <p>20/40 Grade Silica Sand</p>
						<p>SILTY SAND (SM): light olive brown, wet, loose, fine-grained sand            Siltstone, olive brown, wet, hard, platy 36.5'-36.75'</p>	 <p>Schedule 40 PVC 0.010 Slot Screen</p>
40						<p>SILTY SAND (SM): light olive brown, wet, loose to firm, fine-grained sand            SILTY SAND (SM): olive gray, wet, firm, fine-grained sand, layered            CLAY (CH): olive gray, dry, hard, blocky            Total Depth = 40'</p>	 <p>6" End Cap</p>
45							
50							
55							

WELL3



PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. AP PZ-4</b>	
BORING LOCATION: <b>Southwest Corner of Ash Ponds</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>6/2/2016</b>	DATE FINISHED: <b>6/2/2016</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>45.0</b>	SCREEN INTERVAL (ft.): <b>38.5'-43.5'</b>
DRILLING EQUIPMENT: <b>8 5/8" OD HSA Truck Mounded Rig</b>		DEPTH TO WATER ATD: <b>40</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot			
					Clay and gravel fill to 3'	
5					SANDY CLAY (CL): light yellowish-brown, moist, stiff, fine-grained sand  Interbedded sandstone and SANDY CLAY (CL): light yellowish-brown, moist, hard, fine-grained sand  SANDY CLAY (CL): light yellowish-brown, moist, stiff, fine-grained sand, ferrous partings	2" Diameter PVC
10					SANDY CLAY (CL): light yellowish-brown, moist, stiff to 14.5', hard to 15', fine-grained sand, ferrous staining, reddish-brown with increased clay content at 14.5-15'	
15					SANDY CLAY (CL): olive brown, dry, hard, very fine-grained sand, discontinuous silt and sand partings	Grout
20					SANDY CLAY (CL): olive brown, dry, very stiff, fine-grained sand	
25					Lignite, black, dry, hard 23.5'-25' - 2" sand and clay lenses	

WELL3


DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						Lignite, dark brown and black, dry, stiff, few interbedded ironstone, sand, clay (thin beds-large majority lignite 25'-30')	<p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
						Sandstone: olive brown, moist, hard	
35						Lignite, brown to dark brown, dry, stiff 31'-32.75'	<p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
						Interbedded olive brown sand, brown clay and lignite Lignite, brown to dark brown, dry, stiff, platy 33'-35' Lignite, brown to dark brown, dry, stiff, blocky 35'-36'	
40						Interbedded sandy clay, lignite (thin beds), medium gray sand, fine-grained sand, dark brown clay and lignite	<p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
						Lignite, brown to dark brown, dry, stiff, blocky 39'-40'	
45						Sand interbedded with lignite, black, wet, loose, fine-to medium-grained Lignite, black dry, very stiff 41'-41.75'	<p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
						SANDY SILT (ML): olive gray, slightly moist, stiff, very fine-grained sand	
55						Total Depth = 45'	

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. SFL MW-2</b>	
BORING LOCATION: <b>South Side of Landfill F, West of Outfall</b>		GROUND SURFACE ELEVATION AND DATUM: 269'	
DRILLING CONTRACTOR: <b>Vortex Drilling</b>		DATE STARTED: <b>3/16/16</b>	DATE FINISHED: <b>3/16/16</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>50.0</b>	SCREEN INTERVAL (ft.): <b>16'-21'</b>
DRILLING EQUIPMENT: <b>4 1/4 ID HSA ( 8" Borehole)</b>		DEPTH TO WATER ATD: <b>17.5'</b>	CASING:
SAMPLING METHOD: <b>Split Spoon</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES		OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation: NA	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot			
5		1/14	0.0	CLAY CH): dark gray, moist, soft, grading to yellowish-brown at 2'	Concrete 8" Diameter PVC
		3/7 50/1"	0.0	CLAYEY SILTY SAND (SM-SC): light yellowish-brown, dry, hard, platy, fine-grained sand	
10		50/1"	3.0	SANDY SILT (ML): pale yellow, moist, hard, very fine-grained sand	Bentonite
		50/5"	3.0	SILT (ML): pale yellow, moist, hard, very fine-grained sand	
		21/35	0.8	SILT (ML): pale yellow, moist to wet, hard, very fine-grained sand	
15		11/ 24/ 30	5.0	SANDY SILT (ML): pale yellow, moist to wet, hard, wet to 13', then very moist, siltier-a trace of clay (unconsolidated)	12/20 Grade Sand
		30/ 50/2"	4.3	SILTY SAND (SM): light yellowish-brown, moist, hard, unconsolidated, very fine- to fine-grained sand, trace iron oxide staining	
20		19/ 31/ 32	3.8	SILTY SAND (SM): light yellowish-brown, moist to wet, hard, unconsolidated, very fine- to fine-grained sand, iron oxide staining 19-20'	0.010 Slot Schedule 40 PVC 5.5" End Cap
		20/ 50/4"	3.9	SANDY SILTY (SM): light yellowish-brown, wet, unconsolidated, hard, iron oxide staining	
25		41/ 60/6"	2.3	SILTY CLAY (CL): brown, dry, hard at 22.25 SANDY SILTY CLAY (CL): dark gray, dry, hard, bedding planes SANDY SILTY CLAY (CL): dark gray, dry, hard, bedding	

WELL3

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot			
30			20/ 50/5"	3.7	CLAY (CH): dark gray, dry, hard, lenses of sandy clay, fine-grained sand	 <p>Bentonite</p>
			15/ 21/ 37	3.2	SANDY CLAY (CL): olive gray, moist (clayey interval, dry), hard, fine-grained sand	
		15/ 21/ 21	2.0	SANDY CLAY (CL): olive gray, dry, hard, fine-grained sand		
				Slightly SANDY CLAY (CL): dark gray, dry, hard, fine-grained sand		
		12/ 29/ 40	2.5	SILTY CLAY (CH): dark gray, dry, hard, thin linear structures in the clay		
35		20/20 60/6"	2.0	SILTY CLAY (CH): olive gray, dry, hard, silt lenses at 35.5', moist		
				SILTY CLAY (CH): olive gray, dry, hard, silt lenses <1/4, thin, dry		
		10/ 17/ 17	1.1			
40		10/ 11/ 15	1.9	SILTY CLAY (CH): olive gray, moist, firm to hard, few silt partings		
		8/ 12/ 15	2.1	SILTY CLAY (CH): olive gray, moist, firm to hard, few silt partings, one pyrite nodule		
45		12/ 12/ 17	2.2	CLAY (CH): olive gray, moist, firm to hard, silt partings		
				CLAY (CH): olive gray, moist, firm to hard, few silt partings		
50		10/ 12/ 31	2.2			
	Total Depth = 50'					
55						

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. SFL MW-3</b>	
BORING LOCATION: <b>Southeast of Landfill F</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/31/16</b>	DATE FINISHED: <b>5/31/16</b>
DRILLING METHOD: <b>CME 75 HSA (Buggy Rig)</b>		TOTAL DEPTH (ft.): <b>25.0</b>	SCREEN INTERVAL (ft.): <b>19.5'-24.5'</b>
DRILLING EQUIPMENT: <b>CME 75 8 5/8" OD HSA</b>		DEPTH TO WATER ATD: <b>22</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot				
					SILTY SAND (SM): light yellowish-brown, moist, loose, fine-grained sand, trace ferrous staining	<p>2" Diameter PVC</p> <p>Grout</p> <p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
5					SANDY CLAY (CH): brown mottled with blackish-brown, moist, firm, fine-grained sand, minor ferrous staining SANDY CLAY (CH): brown, mottled, moist, firm, fine-grained sand	
10					SANDY CLAY (CL): yellowish-brown, slightly moist, fine-grained sand, bedding planes, stiff Slightly SANDY SILTY CLAY (CL): yellowish-brown, slightly moist, very firm, fine-grained sand	
15					SANDY SILTY CLAY (CL): yellowish-brown, slightly moist, stiff, very fine-grained sand, few bedding planes	
20					Interbedded sandy clay and sandstone, reddish-brown, hard to very stiff, fine-grained sand SILTY SAND (SM): light olive brown, wet, loose to firm, fine-grained sand	
25					CLAY (CL): light to olive green, dry, hard Total Depth = 25'	

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. SFL MW-4</b>	
BORING LOCATION: <b>South of Landfill F</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/31/16</b>	DATE FINISHED: <b>5/31/16</b>
DRILLING METHOD: <b>CME 75 HSA</b>		TOTAL DEPTH (ft.): <b>40.0</b>	SCREEN INTERVAL (ft.): <b>34.5'-39.5</b>
DRILLING EQUIPMENT: <b>CME 75 8 5/8" OD HSA</b>		DEPTH TO WATER ATD: <b>36</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>






DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter. Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Sample	Blows/ Foot				
5					<p>CLAYEY SAND (SC): medium gray, moist, firm, fine-grained sand</p> <p>Interbedded silty sand and sandstone, medium gray, slightly moist, firm to hard, fine-grained</p> <p>CLAYEY SILTY SAND (SC-SM): medium gray, slightly moist, very firm, fine-grained sand</p> <p>SANDY CLAY (CL): light olive brown, dry, hard, fine-grained sand, ferrous staining</p> <p>SANDY SILTY CLAY (CL): light olive brown, slightly moist, very fine-grained sand</p>	<p>2" Diameter PVC</p> <p>Grout</p>	
10					<p>SANDY SILTY CLAY (CL): light olive brown, slightly moist, very fine-grained sand, minor ferrous staining</p>		
15					<p>SANDY SILTY CLAY (CL): brown, dry, very stiff, bedding planes, fine-grained sand</p>		
20					<p>SANDY CLAY (CL): dark olive brown, dry, hard, bedding planes, trace of gypsum, fine-grained sand Lignite lense, dark gray to black, loose to firm</p> <p>SILTY SAND (SM): light olive gray, slightly moist, fine-grained sand, bedding planes, firm</p>		
25							

WELL3

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						<p>SILTY SAND (SM): light olive gray, dry, very fine-grained sand, 25'-26' interbedded siltstone</p> <p>CLAYEY SANDY SILT (ML): dark gray, dry, fine-grained sand, discontinuous thin sand lenses</p> <p>SANDY SILTY CLAY (CL): dark gray, dry, very fine-grained sand, discontinuous thin silt lenses</p>	<p>Grout</p> <p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
35						<p>Interbedded clay and sand; clay, black, dry, hard; sand, olive gray, dry, loose, very fine-grained sand</p> <p>SAND (SP): olive gray, wet, loose, very fine-grained sand</p>	
40						<p>SILTY SAND (SM): olive gray, dry, firm, fine-grained sand</p> <p>Total Depth = 40'</p>	
45							
50							
55							

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. SFL MW-5</b>	
BORING LOCATION: <b>Landfill F</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/23/16</b>	DATE FINISHED: <b>5/23/16</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>25.0</b>	SCREEN INTERVAL (ft.): <b>16'-21'</b>
DRILLING EQUIPMENT: <b>8 5/8" OD HSA 2" Rods</b>		DEPTH TO WATER ATD: <b>16</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot				
5					SILTY SAND (SM): dark grayish-brown, moist, loose, fine-grained sand, roots	 2" Diameter PVC Grout
					SANDY CLAY (CH): dark yellowish-brown, moist, soft, fine-grained sand, roots	
10					SILTY SANDY CLAY (CL): yellowish-brown, dark yellowish-brown lenses, moist, fine-grained sand, firm	 Bentonite
					SILTY SANDY CLAY (CL): yellowish-brown, dry, hard, very fine-grained sand, ferrous staining	
					SILTY SAND (SM): light brownish-gray, mottled with brownish-yellow, soft, moist (slightly) increasing clay content to 8.5', fine-grained sand	
15					Slightly CLAYEY SILTY SAND (SM): light olive brown, loose, moist, fine-grained sand	 20/40 Grade Silica Sand
					Slightly CLAYEY SILTY SAND (SM): light olive brown, slightly firm, moist, trace of pebbles	
20					SILTY SAND (SM): light olive brown, wet to very moist, firm, faint stratification, fine-grained sand	 Schedule 40 PVC 0.010 Slot Screen
					SANDSTONE (SS): light yellowish-brown, dry, hard, ferrous staining along fractures, layered	
25					Shale (SILTY CLAY) (CL): gray, dry, hard, very fine-grained sand, silt partings	 6" End Cap
					Total Depth = 25'	

WELL3



PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. SFL MW-6</b>	
BORING LOCATION: <b>Southwest Corner of Landfill</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/23/16</b>	DATE FINISHED: <b>5/23/16</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>20.0</b>	SCREEN INTERVAL (ft.): <b>14.5'-19.5</b>
DRILLING EQUIPMENT: <b>8 5/8" OD HSA Truck Mounded Rig</b>		DEPTH TO WATER ATD: <b>15</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot				
					Sandy Clay fill, few gravel fill to 4.5'	
5					SANDY SILTY CLAY (CL): pale brown, dry, hard, dark gray partings, very fine-grained sand  CLAYEY SAND SILT (ML): pale brown, dry, very stiff to hard, dark gray clay partings, fine-grained sand, increased ferrous staining after 8', few sand partings, wood fragments in a few partings	2" Diameter PVC Grout
10					SILTY SANDY CLAY (CH): pale brown, dry, hard, light brown partings to reddish-brown, fine-grained sand, ferrous staining	Bentonite
15					Layered SILTY SAND (SM) and SANDY SILTY CLAY (CL): pale brown, some brown layers after 17', very moist to dry, fine-grained sand	20/40 Grade Silica Sand
20					SANDY SILTY CLAY (CL): gray silt and sand, dark gray clay, layered, dry, hard, very fine sand  Total Depth = 20'	Schedule 40 PVC 0.010 Slot Screen 6" End Cap
25						

WELL3

PROJECT: TMPA Gibbons Creek Plant Carlos, Texas		<b>Log of Well No. SFL MW-7</b>	
BORING LOCATION: Southeast Side of Landfill F		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: Tolunay-Wong		DATE STARTED: 5/2/17	DATE FINISHED: 5/3/17
DRILLING METHOD: HSA with Continuous Core Borell		TOTAL DEPTH (ft.): 55.0	SCREEN INTERVAL (ft.): 50'-55'
DRILLING EQUIPMENT: CME 75		DEPTH TO WATER ATD:	CASING:
SAMPLING METHOD: 5' x 4.25" OD Core Barrel		LOGGED BY: Daniel B. Haug, P.G.	
HAMMER WEIGHT: NA	DROP: NA	RESPONSIBLE PROFESSIONAL: Daniel B. Haug, P.G.	REG. NO. 1773

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot			
0					Grass at surface	
2.6					SILTY SAND (SM): yellowish-brown, dry, firm, very fine-grained sand (fill)	
5					SANDY CLAY (CH): gray, slightly moist, firm, very fine-grained sand	8" Diameter PVC
10					SANDY CLAY (CH): brown, slightly moist to moist, firm, olive gray mottling and some ferrous staining, very fine-grained sand, fill to approximately 12'	
15					SANDY CLAY (CL): brown, slightly moist, very fine-grained sand, some lamination, couple of thin greenish-sand lenses	
20					CLAY (CL): dark brown, slightly moist, very fine-grained sand intervals (thin)	
25					SANDY CLAY (CL) with lignite fragments: very dark brown, hard, very fine-grained sand, slightly moist to dry - Layered sand and clay with lignite 19.5'-20', very dark brown to light gray, hard, slightly moist, pyrite nodules	Bentonite Grout
30					CLAY (CH): very dark gray, dry, hard, very thin sand lenses, greenish-gray, lignite fragments along bedding planes, platy	
					CLAY (CH) with interbedded thin sand lenses: very dark gray, dry, hard, very fine-grained sand, lignite fragments along bedding planes in the clay, clay breaks along horizontal laminae, platy	

WELL3

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
35					0.3	CLAY (CL): with numerous thin sand lenses interbedded with clay: very dark gray clay, greenish-gray sand, dry, hard, lignite fragments along bedding planes in the clay, very fine-grained sand, platy	<p>2" Schedule 40 PVC Riser</p> <p>Bentonite Chips</p> <p>16/30 Grade Sand</p> <p>2" Schedule 40 PVC Screen 0.010 Slot</p> <p>5.5" End Cap</p>
40					0.3	CLAY (CH): with sand partings: very dark gray, dry, hard, very fine-grained sand, lignite fragments along bedding planes in the clay, platy, sand greenish-gray	
45					0.2	CLAY (CH) with SAND partings: very dark gray, dry, hard, very fine-grained sand, lignite fragmenst along bedding planes in the clay, platy, sand greenish-gray	
50					0.2	SAND (SP): olive gray, wet, loose, fine- to very fine-grained sand	
55					0.2	CLAY (CH): dark greenish-gray, dry to hard at 46' CLAY (CH): very dark gray, dry, hard, platy	
60					0.2	SILTY SAND (SM): dark gray, wet, loose, very fine- to fine-grained sand Interbedded SAND (SP) and lignite: olive gray, wet, loost to firm 2" lignite seam SAND (SP) with thin lignite lenses, olive gray, wet, loose to firm	
65						Total Depth = 55'	

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. SSP/AP MW-1</b>	
BORING LOCATION: <b>North of Sludge Pond</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>5/25/16</b>	DATE FINISHED: <b>5/26/16</b>
DRILLING METHOD: <b>HSA</b>		TOTAL DEPTH (ft.): <b>40.0</b>	SCREEN INTERVAL (ft.): <b>29.5'-39.5'</b>
DRILLING EQUIPMENT: <b>8 5/8" OD HSA Truck Mounded Rig</b>		DEPTH TO WATER ATD: <b>30</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample Blows/ Foot				
					Silty sand, fly ash and sandy clay, fill to 3.5'	
5					SANDY CLAY (CL): light yellowish-brown, moist, very stiff, fine-grained sand SILT (ML): yellowish-red, moist, firm to hard, after 3" grading to clay, yellowish-red, moist, hard SANDY CLAY (CL): reddish-brown, moist, very stiff, fine-grained sand	2" Diameter PVC
10					Slightly SANDY CLAY (CH): reddish-brown, moist, very stiff, very fine-grained sand	
15					Lignite, black, dry, hard 12'-16'	Grout
20					Slightly SANDY CLAY (CH): dark grayish-brown, dry, hard, very fine-grained sand	
25					SANDY CLAY (CL): dark grayish-brown, moist, hard, fine-grained sand, lithofied sandy lenses from 20.5' to 25', sandier and softer toward 25', platy where hard	

WELL3

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
						<p>SILTY SAND (SM): dark olive brown, slightly moist, hard, platy when hard, fine-grained sand</p>	<p>Bentonite</p> <p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
30					<p>Slightly SILTY SAND (SM): dark olive brown, wet, loose, fine-grained sand</p>		
35					<p>CLAYEY SILTY SAND (SM-SC): dark olive brown, dry to moist, fine-grained sand, firm</p>		
40					<p>Total Depth = 40'</p>		
45							
50							
55							

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>			<b>Log of Well No. SSP MW-2</b>		
BORING LOCATION: <b>West of Center of Scrubber Sludge Pone</b>			GROUND SURFACE ELEVATION AND DATUM:		
DRILLING CONTRACTOR: <b>Best Drilling</b>			DATE STARTED: <b>6/2/06</b>	DATE FINISHED: <b>6/2/06</b>	
DRILLING METHOD: <b>CME 75 HSA</b>			TOTAL DEPTH (ft.): <b>45.0</b>	SCREEN INTERVAL (ft.): <b>38.5'-43.5'</b>	
DRILLING EQUIPMENT: <b>CME 75 8 5/8" OD HSA</b>			DEPTH TO WATER ATD: <b>30</b>	CASING:	
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>			LOGGED BY: <b>Daniel B. Haug, P.G.</b>		
HAMMER WEIGHT: <b>NA</b>		DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>	

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot			
5					9" ash, black, loose  SANDY CLAY (CL): yellowish-brown, moist, firm, fine-grained sand, few pebbles  SANDY CLAY (CL): medium gray, moist, firm, fine-grained sand, few pebbles SANDY CLAY (CL): brown, moist, firm, fine-grained sand, few small gravel	 2" Diameter PVC  Grout
10					SANDY CLAY (CH) with small gravel: brown, moist, firm to stiff, fine-grained sand with pebbles and small gravel, clay clasts, some red and greenish-gray streaking, trace yellow nodules	
15					SANDY SILTY CLAY (CL): brown, moist, stiff, fine-grained sand, trace roots, few bedding planes	
20					SILTY SAND (SM): light olive brown, moist, firm, fine-grained sand, bedding planes, brown organic lenses, very thin	
25						

WELL3

DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						CLAYEY SILTY SAND (SC-SM): light olive brown, moist, firm, fine-grained sand	<p>Grout</p> <p>Bentonite</p> <p>20/40 Grade Silica Sand</p>
						SILTY SAND (SM): light olive brown, wet, 30'-33', sandstone at 33', fine-grained sand	
35						Slightly SILTY SAND (SM): light olive brown, slightly moist, firm, fine-grained sand	
40						SANDY CLAY (CH) with few gravel: reddish-brown, wet, firm	<p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
						SANDY CLAY (CH): dark olive brown, moist, stiff, fine-grained sand	
45						CLAYEY SILTY SAND (SM-SC): dark olive brown, dry, dense, fine-grained sand	
						Total Depth = 45'	
50							
55							

WELL3

PROJECT: <b>TMPA Gibbons Creek Plant Carlos, Texas</b>		<b>Log of Well No. SSP MW-3</b>	
BORING LOCATION: <b>Southwest Corner of Scrubber Sludge Pond</b>		GROUND SURFACE ELEVATION AND DATUM:	
DRILLING CONTRACTOR: <b>Best Drilling</b>		DATE STARTED: <b>6/3/16</b>	DATE FINISHED: <b>6/3/16</b>
DRILLING METHOD: <b>CME 75 HSA</b>		TOTAL DEPTH (ft.): <b>45.0</b>	SCREEN INTERVAL (ft.): <b>39.5'-44.5'</b>
DRILLING EQUIPMENT: <b>CME 75 8 5/8" OD HSA</b>		DEPTH TO WATER ATD: <b>33</b>	CASING:
SAMPLING METHOD: <b>5' x 4" Core Barrel</b>		LOGGED BY: <b>Daniel B. Haug, P.G.</b>	
HAMMER WEIGHT: <b>NA</b>	DROP: <b>NA</b>	RESPONSIBLE PROFESSIONAL: <b>Daniel B. Haug, P.G.</b>	REG. NO. <b>1773</b>

DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.  Surface Elevation:	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot			
					Gravelly sandy clay at surface to 1.5'	
5					SANDY CLAY (CL): yellowish-brown, moist, stiff, fine-grained sand	2" Diameter PVC
					SANDY CLAY (CL) with gravel: yellowish-brown, moist, stiff, fine-grained sand	
10					CLAY and SANDY CLAY (CL-CH): yellowish-brown, reddish-brown, reddish-gray layers (fill), moist, stiff, fine-grained sand	
					Probably fill above 14'	
15					Slightly SANDY CLAY (CH): olive gray to 17.5', moist, stiff, fine-grained sand	Grout
					SANDY CLAY (CL): reddish-yellow, moist, stiff, fine-grained sand	
20					SANDY CLAY (CL): light reddish-brown, dry, stiff, fine-grained sand	
25						

WELL3



DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						SANDY CLAY (CL): light brown, dry, hard  Sandstone, light brown, dry, hard 29.5'-30'  1" of sandstone in core barrel, loose, fine-grained wet sand washed out of core barrel	<p>Grout</p> <p>Bentonite</p>
35						SILTY SAND (SM): light olive brown, wet, soft, fine-grained sand	
40						SILTY SAND (SM): light olive brown, wet, soft, fine-grained sand  1" lignite seam, brown, wet, soft at 41.75, very thin lignite lenses at 42' and 43.5'	<p>20/40 Grade Silica Sand</p> <p>Schedule 40 PVC 0.010 Slot Screen</p>
45						SILTY SAND (SM): light olive brown, wet, stiff, fine-grained sand  Total Depth = 45'	<p>6" End Cap</p>
50							
55							

WELL3

PROJECT: TMPA Gibbons Creek Plant Carlos, Texas					<b>Log of Well No. SSP MW-4</b>					
BORING LOCATION: Southeast Corner of Scrubber Sludge Pond					GROUND SURFACE ELEVATION AND DATUM:					
DRILLING CONTRACTOR: Best Drilling					DATE STARTED: 6/3/16		DATE FINISHED: 6/3/16			
DRILLING METHOD: CME 75 HSA					TOTAL DEPTH (ft.): 50.0		SCREEN INTERVAL (ft.): 43'-48'			
DRILLING EQUIPMENT: CME 75 8 5/8" OD HSA					DEPTH TO WATER ATD: 44.75		CASING:			
SAMPLING METHOD: 5' x 4" Core Barrel					LOGGED BY: Daniel B. Haug, P.G.					
HAMMER WEIGHT: NA			DROP: NA		RESPONSIBLE PROFESSIONAL: Daniel B. Haug, P.G.			REG. NO. 1773		
DEPTH (feet)	SAMPLES			OVM Reading	DESCRIPTION				WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Sample	Blows/ Foot		NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	Surface Elevation:				
5					Sand, gravel, clay fill				2" Diameter PVC	
					SANDY CLAY (CH): layered yellowish-brown, moist, stiff, fine-grained sand, probable fill					
					SANDY CLAY - CLAYEY SAND (CH-SC): brown, moist, firm, fine-grained sand, probable fill				Grout	
					SANDY CLAY (CH): brown and olive brown layered (fill); moist, stiff, fine-grained sand					
10					Probably fill above 14'				Grout	
					SANDY CLAY (CL): yellowish-brown, moist, firm, fine-grained sand, black organic streaks					
15					SANDY CLAY (CH): yellowish-red, very moist, fine-grained sand, soft				Grout	
					CLAY (CH): dark reddish-brown, moist, firm					
20					Lignite, black, moist, firm 22.5'-23'				Grout	
					SANDY CLAY (CL): light yellowish-brown, moist, stiff, fine-grained sand					
25										

WELL3


DEPTH (feet)	SAMPLES				OVM Reading	DESCRIPTION NAME (USCS): color, moist, % by wt., plast. density, structure, cementation, react. w/HCl, geo. inter.	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot				
30						SANDY CLAY (CL): light yellowish-brown, moist, very stiff, fine-grained sand, ferrous streaks	<p>Grout</p> <p>Bentonite</p>
35						Lignite, black, moist, firm 34.75'-35.25' SANDY CLAY (CL): dark grayish-brown, dry, hard, fine-grained sand	
40						Lignite, dark brown, dry, hard 38.25'-38.75' SANDY CLAY (CL): dark grayish-brown, dry, hard, fine-grained sand, interbedded black clay lenses Interbedded sand and clay to 44.75'; CLAY (CH): black, dry, hard and; SAND (SP): olive gray, dry, dense	<p>20/40 Grade Silica Sand</p>
45						SAND (SP): olive gray, moist, dense, fine-grained sand, wet	<p>Schedule 40 PVC 0.010 Slot Screen</p> <p>6" End Cap</p>
50						SANDY CLAY (CL): dark gray, moist, wet at 45'-46' (sandier interval), moist to dry below 46', hard, fine-grained sand	
55						Total Depth = 50'	

WELL3



CLIENT Texas Municipal Power Agency		PROJECT Gibbons Creek	PROJECT NO 14578
PROJECT LOCATION Carlos, Texas	COORDINATES N378330 E3339148	GROUND ELEVATION 266.8'	DATE 2-26-88
STRATUM MONITORED Sandstone and clay		INSPECTOR K. M. Blevins-McCosh	
CHECKED BY M. C. Schluter		APPROVED BY L. J. Almaleh	

Page 1 of 2



METHOD OF INSTALLATION: Boring drilled to completion; set riser pipe and screen; placed filter and seal; grouted to surface; poured surface pad

REMARKS: Installed piezometer in fluid-filled hole; added approximately 2 gallons of bentonite pellets for seal but only 9" arrived at 35'- rest hung up- didn't have any more bentonite developed well on 2-27-88 by flushing w/clean water for 3 minutes and blowing it out w/air

P-ST-021

CLIENT							PROJECT			PROJECT NO.		
Texas Municipal Power Agency							Gibbons Creek SES			14578		
PROJECT LOCATION				COORDINATES			ELEVATION (DATUM)		TOTAL DEPTH	DATE START		
Carlos, Texas				N378329 E3339148			266.7'		50'	2-26-88		
SURFACE CONDITIONS							INSPECTOR			DATE FINISH		
Clearing in woods							K. M. Blevins-McCosh			2-26-88		
SAMPLING							CHECKED BY			APPROVED BY		
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP RECV	M. C. Schluter			L. J. Almaleh		
CORING							DEPTH IN FEET	SAMPLE TYPE	CLASSIFICATION OF MATERIAL		REMARKS	
CORE SIZE	RUN NO.	RUN LENG	RUN RECV	RQD RECV	% RECV	RQD		GRAPHICS LOG				
TW	1					1.6	1		Silty CLAY; reddish-brown; stiff; high plasticity; moist; organics; roots; iron staining (Top soil)		Advanced boring w/4 1/2" rotary wash	
TW	2					0.8	2		Grading brown w/some sand; trace gravel below 2'		pp. 2.75	
TW	3					1.1	3		Grading w/some sandstone seams and some gravel w/trace roots below 4'			
TW	4					1.2	4					
TW	5					1.4	5			Sandy CLAY; tan to buff; stiff; low plasticity; moist; iron stained; w/trace gravel and some silt		
TW	6					1.2	6			Clayey SILT; tan to buff; hard; high plasticity; moist; some sand; iron staining especially on joints; joints spaced 2-6" horizontal		
TW	7					1.5	7		Interbedded with silty sand below 10'			
TW	8					1.3	8		Grading tan to brown with iron nodules and few cemented sand fragments; platy below 12'			
TW	9					1.5	9		Blocky structure below 14'			
TW	10					1.5	10		Cemented sand grades out below 14';			
TW	11					1.8	11		Cemented sand layer at 18'			
TW	12					1.9	12		CLAY; greenish-grey; hard; high plasticity; moist w/silt filled joints and some silt; trace sand; trace lignite 22'-24'			
TW	13					1.9	13		Grading greenish-grey and dark grey banded below 23'			
TW	14					1.7	14		Slickensided below 26'			
TW	15					2.0	15					


P I S E I D

CLIENT							PROJECT				PROJECT NO.		
Texas Municipal Power Agency							Gibbons Creek SES				14578		
PROJECT LOCATION				COORDINATES			ELEVATION (DATUM)		TOTAL DEPTH	DATE START			
Carlos, Texas				N378329 E3339148			266.7'		50'	2-26-88			
SURFACE CONDITIONS							INSPECTOR				DATE FINISH		
Clearing in woods							K. M. Blevins-McCosh				2-26-88		
SAMPLING							CHECKED BY			APPROVED BY			
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP RECV	M. C. Schluter			L. J. Almaleh			
CORING							DEPTH IN FEET	SAMPLE TYPE	CLASSIFICATION OF MATERIAL			REMARKS	
CORE SIZE	RUN NO.	RUN LENG	RUN RECV	RQD RECV	% RECV	RQD	DEPTH IN FEET	GRAPHICS LOG					
TW	16					1.8	1					pp. 4+	
TW	17					1.9	2		Trace pyrite below 32'				
TW	18					1.9	3						
TW	19					2.0	4		Bands grading out below 34'				
TW	20					1.7	35						
TW	21					1.9	6						
TW	22					2.0	7						
TW	23					1.1	8					pp. 4+	
TW	24					0	9						
							40						
							1		Trace lignite below 41'				
							2		Grading dark grey below 42'; 1/2" silt seam at 42.3'				
							3						
							4					pp. 4+	
							45		Silty CLAY; dark grey; hard; high plasticity; dry; some iron staining				
							6						
							7					TW 24 no sample cored w/2' core barrel	
3"	1	2	48' 1.3	0.3	65	17	8						
			50'				9			SANDSTONE; argillaceous; grey; fine grained; slightly weathered; w/trace lignite; horizontal joints			Bottom of boring 49.8'. Groundwater level unknown. Reamed 0-3' w/6 7/8" bit Reamed 3-50' w/4 1/2" bit. Installed 2-20' sections of 2" PVC pipe; 1-7.2' section of 2" PVC and 1-5' screen.
							50						
							1						
							2						
							3						
							4						
							55						
							6						
							7						
							8						
							9						
							60						

F I S H I D





CLIENT Texas Municipal Power Agency		PROJECT Gibbons Creek	PROJECT NO 14578
PROJECT LOCATION Carlos, Texas	COORDINATES N378200 E3342496	GROUND ELEVATION 261.5'	DATE 2-23-88
STRATUM MONITORED Sandstone		INSPECTOR K. M. Blevins-McCosh	
CHECKED BY M. C. Schluter		APPROVED BY L. J. Almaleh	



METHOD OF INSTALLATION: Boring drilled to completion; set riser pipe and screen; placed filter and seal; grouted to surface; poured surface pad.

REMARKS: Flushed cuttings from hole; hole remained fluid filled during installation. Developed well on 2-27-88 by flushing well with clean water for 6 min. blew out water from well with air compressor water level recorded at 23'-10" from TOC

P-ST-021B

CLIENT							PROJECT				PROJECT NO.	
Texas Municipal Power Agency							Gibbons Creek SES				14578	
PROJECT LOCATION				COORDINATES			ELEVATION (DATUM)		TOTAL DEPTH	DATE START		
Carlos, Texas				N378200 E3342496			261.5'		35.0'	2-23-88		
SURFACE CONDITIONS							INSPECTOR				DATE FINISH	
Open pasture							K. M. Blevins-McCosh				2-23-88	
SAMPLING							CHECKED BY		APPROVED BY			
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP RECV	M. C. Schluter		L. J. Almaleh			
CORING							DEPTH IN FEET	SAMPLE TYPE	CLASSIFICATION OF MATERIAL		REMARKS	
CORE SIZE	RUN NO.	RUN LENG	RUN RECV	RQD RECV	% RECV	RQD		GRAPHICS LOG				
							1		Undifferentiated overburden		Advanced hole using 4 1/2" rotary wash	
TW	1					1.2	2		Silty CLAY; brown; medium dense; stiff to hard; low plasticity; moist; some sand Grading to more silt at 3'-3.5'			
TW	2					0.8	4					
TW	3					0.5	6		Sandy CLAY; tan to brown; hard; low plasticity; moist; trace silt		pp. 4+	
TW	4					0.8	8					
3"	1	2	10'	0	0	0	10		Clayey SAND; tan to brown; poorly graded; fine grained; some silt; iron staining		Tried to push TW Tried SPT - cored at 10' so reamed w/rotary wash looked at cuttings	
3"	2	2	12'	0	65	0	1		SANDSTONE; argillaceous; yellowish-tan; fine to medium grained; iron staining; highly weathered		Sample recovery below 12' in 1-3" sections	
3"	3	2	14'	0	60	0	2		Argillaceous grading out below 14'			
3"	4	2	16'	0	0	0	3		Grading grey below 16'			
3"	5	2	18'	0	0	0	4		Iron staining on joints below 20'		Missed sample at 18-20' rotary washed. Continued drilling with 3" diameter 5' core barrel below 20'.	
3"	6	5	20'	0.33	90	7	6		Lignite partings starting at 21.7'			
3"	7	5	25'	0.83	80	12	7		Grading greenish-grey below 23' and slightly argillaceous			
			30'				8		Lignite partings grading out below 27.5'			

F I S H O




CLIENT Texas Municipal Power Agency							PROJECT Gibbons Creek SES			PROJECT NO. 14578	
PROJECT LOCATION Carlos, Texas				COORDINATES N378200 E3342496			ELEVATION (DATUM) 261.5'		TOTAL DEPTH 35.0'	DATE START 2-23-88	
SURFACE CONDITIONS Open pasture							INSPECTOR K. M. Blevins-McCosh			DATE FINISH 2-23-88	
SAMPLING			CHECKED BY M. C. Schluter				APPROVED BY L. J. Almaleh				
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP RECV	DEPTH IN FEET		SAMPLE TYPE GRAPHICS LOG		REMARKS
CORING											
CORE SIZE	RUN NO.	RUN LENG	RUN RECV	RQD RECV	% RECV	RQD			CLASSIFICATION OF MATERIAL		
3"	8	5	30' 2.2	0	44	0	1	Horizontal fractures spaced generally from 1-3" apart; numerous lignite partings below 30'			
			35'				2				
							3				
							4				
							6			Bottom of boring 35'. Ground water level unknown. Reamed hole using 4 1/2" bit. Flush cuttings out of hole installed 1-20' section and 1-11' section of 2" PVC and 5' section of screen.	
							7				
							8				
							9				
							40				
							1				
							2				
							3				
							4				
							45				
							6				
							7				
							8				
							9				
							50				
							1				
							2				
							3				
							4				
							55				
							6				
							7				
							8				
							9				
							60				

D I S T R I B U T I O N



CLIENT Texas Municipal Power Agency		PROJECT Gibbons Creek		PROJECT NO 14578
PROJECT LOCATION Carlos, Texas		COORDINATES N379581 E3339416	GROUND ELEVATION 261.7'	DATE 2-25-88
STRATUM MONITORED Sandstone			INSPECTOR K. M. Blevins-McCosh	
CHECKED BY M. C. Schluter		APPROVED BY I. J. Almaleh		



METHOD OF INSTALLATION: Boring drilled to completion; set riser pipe and screen; placed filter and seal; grouted to surface; poured surface pad

REMARKS: Cuttings washed from hole; piezometer installed in fluid-filled hole; well developed on 2-27-88 by flushing hole w/clean water for 8 min. and pumping until dry. Water level recorded at 38.2' from TOC.

P-ST-02

CLIENT						PROJECT				PROJECT NO.		
Texas Municipal Power Agency						Gibbons Creek SES				14578		
PROJECT LOCATION			COORDINATES			ELEVATION (DATUM)		TOTAL DEPTH	DATE START			
Carlos, Texas			N379581 E3339416			261.7'		39.0'	2-25-88			
SURFACE CONDITIONS						INSPECTOR				DATE FINISH		
Clearing in woods						K. M. Blevins-McCosh				2-25-88		
SAMPLING						CHECKED BY		APPROVED BY				
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP RECV	M. C. Schluter		L. J. Almaleh			
CORING						DEPTH IN FEET	SAMPLE TYPE		CLASSIFICATION OF MATERIAL	REMARKS		
CORE SIZE	RUN NO.	RUN LENG	RUN RECV	RQD RECV	% RECV		RQD	GRAPHICS LOG				
TW	1					0.7	1		Silty <u>CLAY</u> ; dark brown; medium dense; high plasticity; moist; organics; roots (Top soil)	Boring advanced using 6 7/8" rotary wash		
TW	2					1.5	2		<u>CLAY</u> ; dark brown; stiff; high plasticity; moist; some silt			
TW	3					1.1	3			pp. 1.25		
TW	4					1.8	4		Trace gravel and iron staining below 4'	pp. 1.5		
TW	5					1.7	5					
TW	6					1.8	6					
TW	7					1.5	7		Silty <u>CLAY</u> ; brown; stiff; high plasticity; moist; iron staining; jointed	pp. 2.0		
TW	8					1.7	8		Gypsum seam at 7.5' and 9'; slickensided below 7'			
TW	9					1.7	9					
TW	10					1.7	10		Horizontal and 45° to vertical joints below 10' filled w/gypsum crystals and iron staining	pp. 2.5		
TW	11					1.6	1			pp. 2.75		
TW	12					1.3	2					
TW	13					1.3	3		Gypsum filled vertical joint at 14'- joint is 4" long; banded brown and dark brown below 14'. Gypsum filled joint spacing generally 8"-1.5'	pp. 2.75 pp. 3.5		
TW	14					1.2	4					
TW	15					0.4	6			pp. 3.0		
							7					
							8					
							9		<u>CLAY</u> ; olive grey to dark grey; hard; high plasticity; moist; with silt seams on joints below 20'; trace iron staining; trace sand in joints; occasional silty sand pockets below 16'; thinly bedded	pp. 4+		
							20					
							1			pp. 4+		
							2					
							3			pp. 4+		
							4					
							25			pp. 4+		
							6					
							7					
							8					
							9		Lignitic below 29' - lignite seams up to 1"			
							30					


P  
I  
S  
T  
I  
O  
3

CLIENT Texas Municipal Power Agency							PROJECT Gibbons Creek SES			PROJECT NO. 14578	
PROJECT LOCATION Carlos, Texas				COORDINATES N379581 E3339416			ELEVATION (DATUM) 261.7'		TOTAL DEPTH 39.0'	DATE START 2-25-88	
SURFACE CONDITIONS Clearing in woods							INSPECTOR K. M. Blevins-McCosh			DATE FINISH 2-25-88	
SAMPLING							CHECKED BY M. C. Schluter			APPROVED BY L. J. Almaleh	
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP RECV	DEPTH IN FEET	SAMPLE TYPE	CLASSIFICATION OF MATERIAL		REMARKS
CORING							DEPTH IN FEET	GRAPHICS LOG	CLASSIFICATION OF MATERIAL		REMARKS
CORE SIZE	RUN NO.	RUN LENG	RUN RECV	RQD RECV	% RECV	RQD					
3"	1	1	0.2 31'	0	20	0	1	[Pattern]	SANDSTONE; argillaceous; greenish-grey; fine grained; weathered		
TW	16					0.5	2		Clayey SAND; greenish-grey; partially cemented; fine grained; poorly graded; some silt (maybe extremely weathered sandstone)		
3"	2	5	34' 4	1.3	80	26	3	[Pattern]	SANDSTONE; argillaceous; greenish-grey; fine grained; weathered; w/lignite seams; horizontal and vertical joints - weathering on joints		
							4				
			39'				35	[Pattern]			Bottom of boring at 39'. Groundwater level unknown. Reamed hole w/6 7/8" bit. Installed 3-10' sections 4" PVC and 1-5.8' section 4" PVC; set 1-5' section .01" slot screen.
							6				
							7	[Pattern]			
							8				
							9	[Pattern]			
							10				
							11	[Pattern]			
							12				
							13	[Pattern]			
							14				
							15	[Pattern]			
							16				
							17	[Pattern]			
							18				
							19	[Pattern]			
							20				
							21	[Pattern]			
							22				
							23	[Pattern]			
							24				
							25	[Pattern]			
							26				
							27	[Pattern]			
							28				
							29	[Pattern]			
							30				
							31	[Pattern]			
							32				
							33	[Pattern]			
							34				
							35	[Pattern]			
							36				
							37	[Pattern]			
							38				
							39	[Pattern]			
							40				
							41	[Pattern]			
							42				
							43	[Pattern]			
							44				
							45	[Pattern]			
							46				
							47	[Pattern]			
							48				
							49	[Pattern]			
							50				
							51	[Pattern]			
							52				
							53	[Pattern]			
							54				
							55	[Pattern]			
							56				
							57	[Pattern]			
							58				
							59	[Pattern]			
							60				

B I S F I I



CLIENT Texas Municipal Power Agency		PROJECT Gibbons Creek	PROJECT NO 14578
PROJECT LOCATION Carlos, Texas	COORDINATES N381087 E3340991	GROUND ELEVATION 292.3'	DATE 2-17-88
STRATUM MONITORED Clay		INSPECTOR K. M. Blevins-McCosh	
CHECKED BY M. C. Schluter		APPROVED BY L. J. Almaleh	



METHOD OF INSTALLATION: Boring drilled to completion; set riser pipe and screen; placed filter and seal; grouted to within 5' of ground surface filled remaining 5' with dry grout and cuttings

REMARKS: Developed well on 2-27-88 by flushing w/clean water for 7 min.; pumped well dry; water level recorded at 48.5' from TOC.

P-ST-021B

CLIENT							PROJECT				PROJECT NO.	
Texas Municipal Power Agency							Gibbons Creek SES				14578	
PROJECT LOCATION				COORDINATES			ELEVATION (DATUM)		TOTAL DEPTH	DATE START		
Carlos, Texas				N381083 E3340991			292.3'		50.0'	2-17-88		
SURFACE CONDITIONS							INSPECTOR				DATE FINISH	
Clearing in pasture							K. M. Blevins-McCosh				2-17-88	
SAMPLING							CHECKED BY			APPROVED BY		
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP RECV	M. C. Schluter			L. J. Almaleh		
CORING							DEPTH IN FEET	SAMPLE TYPE	CLASSIFICATION OF MATERIAL			REMARKS
CORE SIZE	RUN NO.	RUN LENG	RUN RECV	RQD RECV	% RECV	RQD	DEPTH IN FEET	GRAPHICS LOG	CLASSIFICATION OF MATERIAL			REMARKS
TW	1					1.5	1	10" Undifferentiated overburden				Advanced hole by rotary wash
							2	Silty CLAY; brown; stiff; med. plasticity; very moist; w/some roots				pp. 1.0
TW	2					1.2	3	Roots grade out below 3'				
							4	Grading grey below 2.5' with trace sand				pp. 4+
							5	1" sand layer at 4.25'				
TW	3					1.1	6					pp. 4+
TW	4					0.9	7	Clayey SILT; brown to tan; hard; poorly graded; moist; with sand; trace lignite below 11'				
TW	5					1.2	8					
TW	6					0.9	9					
TW	7					0.7	10					
							1					
							2	CLAY; tan; hard; high plasticity; moist with cemented sand stringers; platy in areas with iron staining at plate faces				pp. 4+
TW	8					1.3	3					
							4					
							15	Grading silty with 2" sandy silt seam at approximately 15.7'				
TW	9					1.5	6					
							7	Clayey SILT; tan to buff; hard; low plasticity; moist; with some sand and iron staining on plates				
							8					
TW	10					0.9	9	Sandy SILT; tan to buff; poorly graded; moist with some clay; trace iron staining				
TW	11					0.8	20					
							1	Silty CLAY; brown/tan mottled; hard; high plasticity; moist; with trace sand and iron staining; platy				
							2					
TW	12					1.2	3	3" sandy silt layer at 22.5'; grading brown below 23				
TW	13					1.8	4					
							25	CLAY; brown; hard; high plasticity; moist; iron staining on plates and joints; gypsum crystals at 25.8'				
							6					pp. 4+
TW	14					1.2	7	Clayey SILT; brown; high plasticity; moist; iron staining				
							8					
TW	15					1.4	9	CLAY; greenish-grey; high plasticity; hard; moist; with trace silt; trace iron				
							30					


P  
-  
S  
T  
6  
D

CLIENT							PROJECT			PROJECT NO.	
Texas Municipal Power Agency							Gibbons Creek SES			14578	
PROJECT LOCATION				COORDINATES			ELEVATION (DATUM)		TOTAL DEPTH	DATE START	
Carlos, Texas				N381083 E3340991			292.3'		50.0'	2-17-88	
SURFACE CONDITIONS							INSPECTOR			DATE FINISH	
Clearing in pasture							K. M. Blevins-McCosh			2-17-88	
SAMPLING							CHECKED BY			APPROVED BY	
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP RECV	M. C. Schluter			L. J. Almaleh	
CORING							DEPTH IN FEET	SAMPLE TYPE	CLASSIFICATION OF MATERIAL		REMARKS
CORE SIZE	RUN NO.	RUN LENG	RUN RECV	RQD RECV	% RECV	RQD	DEPTH IN FEET	GRAPHICS LOG	CLASSIFICATION OF MATERIAL		REMARKS
TW	16					2.0	1	[Hatched Log]			
							2				
TW	17					1.8	3				
							4				
TW	18					1.8	35		Grading to trace silt below 35'		
							6				
TW	19					1.7	7				
							8		Grading to laminated banded (greenish-grey and grey) below 38' with trace lignite at 39.8';		
TW	20					1.9	9				
							40				
TW	21					1.9	1				
							2				
TW	22					1.8	3				
							4		Banding grading out below 44'		
TW	23					2.0	45				
							6				pp. 4+
TW	24					1.8	7		Banded below 47'		
							8				
TW	25					1.6	9				
							50				Bottom of boring at 50'. Groundwater level unknown. Hole reamed using 6 1/2" diameter auger bit.
							1				
							2				
							3				
							4				Set 4-10' and 1-4.6' section of 4" diameter schedule 40 threaded flush-jointed PVC pipe, 5' screen.
							55				
							6				
							7				
							8				
							9				
							60				

A I S E 6 D



CLIENT Texas Municipal Power Agency		PROJECT Gibbons Creek	PROJECT NO 14578
PROJECT LOCATION Carlos, Texas	COORDINATES N381539 E3342922	GROUND ELEVATION 269.1'	DATE 2-18-88
STRATUM MONITORED Clay		INSPECTOR K. M. Blevins-McCosh	
CHECKED BY M. C. Schluter		APPROVED BY L. J. Almaleh	



METHOD OF INSTALLATION: Boring drilled to completion; set riser pipe and screen; placed filter and seal; grouted to surface; poured surface pad.

REMARKS: Riser pipe started to rise so had to fill with water during installations; well developed on 2-27-88 by flushing w/clean water for 7 min., and then pumping well dry. Water level 50' from TOC.

P-ST-021B



CLIENT							PROJECT			PROJECT NO.	
Texas Municipal Power Agency							Gibbons Creek SES			14578	
PROJECT LOCATION				COORDINATES			ELEVATION (DATUM)		TOTAL DEPTH	DATE START	
Carlos, Texas				N381539 E3342922			269.1		50.0'	2-17-88	
SURFACE CONDITIONS							INSPECTOR			DATE FINISH	
Clearing in pasture							K. M. Blevins-McCosh			2-17-88	
SAMPLING							CHECKED BY		APPROVED BY		
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP REC'D	M. C. Schluter		L. J. Almaleh		
CORING							DEPTH IN FEET	SAMPLE TYPE	CLASSIFICATION OF MATERIAL		REMARKS
CORE SIZE	RUN NO.	RUN LENG	RUN REC'D	RQD REC'D	% REC'D	RQD	GRAPHICS LOG				
							1		Undifferentiated overburden		Boring advanced using 4 1/2" rotary wash
							2				
TW	1					0.6	3		Sandy SILT; tan; poorly graded; moist; with cemented sand stringers; some clay; iron staining		
TW	2					1.5	5		Clayey SILT; reddish-brown; hard; high plasticity; moist; trace sand; iron staining; grading some sand below 7'		
TW	3					1.3	7				pp. 4+
TW	4					1.7	9		Sandy SILT; reddish-brown; poorly graded; moist; with clay and iron staining; grading to silty clay; interbedding with lignitic clay below 10'; few gypsum crystals		
TW	5					1.3	10				
TW	6					1.5	3		Silty CLAY; dark brown to black; hard; highly plastic; moist; lignitic; iron staining; with trace sand below 16'		pp. 4+
TW	7					0.9	15				
TW	8					0.9	6				pp. 4+
TW	9					0.7	7		Silty SAND; tan; poorly graded; moist; trace clay; iron staining		pp. 4+
TW	10					1.4	8		Clayey SILT; greenish-grey; highly plastic; moist; with trace thin silty sand laminae; trace iron staining		
TW	11					1.8	9				
TW	12					0.8	20		Sandy SILT; greenish-grey; poorly graded; moist; with trace to some clay		
TW	13					1.2	6		Silty CLAY; greenish-grey; high plasticity; moist; with some sandy silt layers		
TW	14					1.3	7				
							8				
							9				
							30				

P  
-  
S  
T  
6  
D

CLIENT Texas Municipal Power Agency		PROJECT Gibbons Creek SES		PROJECT NO. 14578
PROJECT LOCATION Carlos, Texas		COORDINATES N381539 E3342922	ELEVATION (DATUM) 269.1	TOTAL DEPTH 50.0'
SURFACE CONDITIONS Clearing in pasture		INSPECTOR K. M. Blevins-McCosh		DATE FINISH 2-17-88

SAMPLING						CHECKED BY M. C. Schluter	APPROVED BY L. J. Almaleh
SAMP TYPE	SAMP NO.	SET 6"	2ND 6"	3RD 6"	N VAL	SAMP RECV	

CORE SIZE	RUN NO.	RUN LENG	CORING			DEPTH IN FEET	SAMPLE TYPE GRAPHICS LOG	CLASSIFICATION OF MATERIAL	REMARKS
			RUN RECV	RQD RECV	% RECV				
TW	15					1.4			
TW	16					1.4		2" sandy silt seam at 32.5'; grading to low plasticity; sandy silt filled fractures spacing about 4" in sample	
TW	17					1.5		Grading to interbedded green and greenish grey silty clay below 34'; trace cemented sand	
TW	18					0.9			
TW	19					2.0		2" sandy silt seam at 37.8' Grading greenish-grey below 38'	
TW	20					2.1		Grading to high plasticity below 40'; sandy silt seam grading out; becoming greenish grey and grey banded clay	
TW	21					2.0			
TW	22					1.7		Slickensides at 44.5'	
TW	23					1.9			
TW	24					1.6			
									Bottom of boring at 50'. Groundwater level unknown. Reamed hole twice using 6 3/4" auger bit. Installed 4-10' and 1-5.5' section of 4" PVC, 1-5' section of screen.

BISHOP

---

**APPENDIX B**

Field Sampling Forms

# DAILY FIELD RECORD



Project and Task Number:	Date:
Project Name:	Field Activity:
Location:	Weather:

PERSONNEL:	Name	Company	Time In	Time Out

### PERSONAL SAFETY CHECKLIST

Steel-toed Boots	Hard Hat	Tyvek Coveralls
Rubber Gloves	Safety Goggles	1/2-Face Respirator

DRUM I.D.	DESCRIPTION OF CONTENTS AND QUANTITY	LOCATION

TIME	DESCRIPTION OF WORK PERFORMED



# Water Level Monitoring Record



Project Name: \_\_\_\_\_ Project and Task Number: \_\_\_\_\_

Date: \_\_\_\_\_ Measured by: \_\_\_\_\_ Instrument Used: \_\_\_\_\_

Note: For your convenience, the following abbreviations may be used.

P = Pumping                      I = Inaccessible                      D = Dedicated Pump  
 ST = Steel Tape                  ES = Electric Sounder                  MP = Measuring Point                  WL = Water Level

Well No.	Time	MP Elevation (feet)	Water Level Below MP (feet)	Water Level Elevation (feet)	Previous Water Level Below MP	Remarks

# WELL SAMPLING AND/OR DEVELOPMENT RECORD



Well ID: \_\_\_\_\_  
 Sample ID: \_\_\_\_\_ Duplicate ID: \_\_\_\_\_  
 Sample Depth: \_\_\_\_\_  
 Project and Task No.: \_\_\_\_\_  
 Project Name: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Sampled By: \_\_\_\_\_  
 Method of Purging: \_\_\_\_\_  
 Method of Sampling: \_\_\_\_\_

Initial Depth to Water: \_\_\_\_\_  
 Depth to Water after Sampling: \_\_\_\_\_  
 Total Depth to Well: \_\_\_\_\_  
 Well Diameter: \_\_\_\_\_  
 1 Casing/Borehole Volume: \_\_\_\_\_  
 (Circle one)  
 4 Casing/Borehole Volumes: \_\_\_\_\_  
 (Circle one)  
 Total Casing/Borehole  
 Volumes Removed: \_\_\_\_\_

Time	Intake Depth	Rate (ml/min)	Cum. Vol. (gal.)	Temp. (°C)	pH (units)	Specific Electrical Conductance (µS/cm)	Dissolved Oxygen (mg/L)	Oxidation-Reduction Potential (mV)	Remarks (color, turbidity, and sediment)
<b>Low Flow Stabilization Criteria</b>				+/- 3%	+/- 0.1	+/- 3%	+/- 10%	+/- 10%	

pH CALIBRATION (choose two)					Model or Unit No.:	
Buffer Solution	pH 4.0	pH 7.0	pH 10.0			
Field Temperature °C						
Instrument Reading						
SPECIFIC ELECTRICAL CONDUCTANCE (SEC) – CALIBRATION					Model or Unit No.:	
KCl Solution (µS/cm=µmhos/cm)	1413 at 25°C	12880 at 25°C				
Field Temperature °C						
Instrument Reading						
ORP/REDOX CALIBRATION		DISSOLVED OXYGEN CALIBRATION		Notes:		
Standard Solution (mV)		Altitude / Salinity %				
Field Temperature °C		Field Temperature °C				
Instrument Reading (mV)		Instrument Reading (mg/L)				
Model or Unit No.:		Model or Unit No.:				

# FIELD INSTRUMENT CALIBRATION SHEET



Project Name: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Project Number: \_\_\_\_\_  
Date: \_\_\_\_\_

Equipment Type: Water Quality Meter  
Manufacturer: Horiba  
Model Number: U-52

Serial Number: \_\_\_\_\_

Calibration (as necessary, minimum twice per day):

Calibration #1	pH	Cond.	Turb.	DO	ORP	Time: _____
Calibration Standard:	<u>4.0</u>	<u>4.49</u>	<u>0.0</u>	<u>--</u>	<u>200-300</u>	
Instrument Reading:	_____					

Calibration (as necessary, minimum twice per day):

Calibration #2	pH	Cond.	Turb.	DO	ORP	Time: _____
Calibration Standard:	<u>4.0</u>	<u>4.49</u>	<u>0.0</u>	<u>--</u>	<u>200-300</u>	
Instrument Reading:	_____					

Calibration (as necessary, minimum twice per day):

Calibration #3	pH	Cond.	Turb.	DO	ORP	Time: _____
Calibration Standard:	<u>4.0</u>	<u>4.49</u>	<u>0.0</u>	<u>--</u>	<u>200-300</u>	
Instrument Reading:	_____					

Calibration (as necessary, minimum twice per day):

Calibration #4	pH	Cond.	Turb.	DO	ORP	Time: _____
Calibration Standard:	<u>4.0</u>	<u>4.49</u>	<u>0.0</u>	<u>--</u>	<u>200-300</u>	
Instrument Reading:	_____					

Date of Last Calibration: \_\_\_\_\_

Date(s) Instrument Used: \_\_\_\_\_

Name of person(s) who calibrated instruments: \_\_\_\_\_

Calibration Standards Used:

- (1) \_\_\_\_\_
- (2) \_\_\_\_\_
- (3) \_\_\_\_\_
- (4) \_\_\_\_\_

Source of Calibration Standards: \_\_\_\_\_

Miscellaneous Comments:

\_\_\_\_\_  
\_\_\_\_\_

Calibrated by: \_\_\_\_\_